Product datasheet Characteristics

NSYS3D12830T

Spacial S3D tspt door w/o mount.plate. H1200xW800xD300 IP66 IK08 RAL7035.





Main

Spacial
Spacial S3D
Multi-purpose
Compact enclosure
1200 mm
800 mm
300 mm
Glazed
Without mounting plate
Standard
Wall-mounting
1 body 2 cable gland plate 1 door 1 lock

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	7
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	2.
Removable parts	Door by hinges Cable gland plate by screws	
Material	Body: steel Door: steel and security glass) ;
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	

Standards	IEC 62208
Product certifications	DNV
	GL
	UL
	BV
	LR
	CUL
Net weight	42 kg

Environment

Electromagnetic compatibility	Electromagnetic field immunity test
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

PCE	
1	
42 kg	
122.6 cm	
82.4 cm	
35.4 cm	
	1 42 kg 122.6 cm 82.4 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months	