



Main

Commercial Status	Commercialised
Range	Spacial S3X
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	400 mm
Nominal width	400 mm
Nominal depth	200 mm
Product installation	Wall-mounting
Device composition	1 door 1 lock (door) 1 body

Complementary

Body type	Gutter shaped front rail Single piece body, cross-shaped structure
Door type	Plain
Number of doors	Front face : 1 door(s)
Door opening	120 °, reversible
Lock type	3 mm double-bar lock
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door fixing: by hinges
Material	Body and door : stainless steel 316L Hinge : stainless steel Lock : zamak
Surface finish	Lock : chromium plated Body and door : Scotch-Brite® brushed
Thickness	1.5 mm

Environment

Standards	IEC 62208
Product certifications	CAN/CSA 22 UL 508 type A
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Environmental characteristic	Corrosive Specific hygiene

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0940 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations