



Main

Commercial Status	Commercialised
Range	Spacial SF
Application	Multi-purpose
Product or component type	Suitable enclosure
Enclosure nominal height	2000 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	500 mm
Installation accessory type	Floor-standing
Device composition	1 mounting plate 1 roof 1 rear panel 1 locking system with handle for door 1 door 1 structure 4 mounting plate bracket 2 sliding rails

Complementary

Structure type	Formed from a single section Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm
Door type	Plain on front
Number of doors	1 on front
Door opening	Reversible 120 °
Lock type	4 points lock, handle with 5 mm double bar insert on front door
Mounting plate description	Plain
Type of gland plate	Without gland plate
Accessibility for operation	Front Rear Sides of enclosure
Removable parts	Mounting plate fixed by screws for mounting plate bracket Sliding rail fixed by screws Mounting plate bracket fixed by screws Door fixed by screws for hinge Roof fixed by screws Rear panel fixed by screws
Material	Polyamide 6 with 30 % fibre glass for handle Zamak for hinge Sheet steel for panels Sheet steel for door Galvanised steel for uprights Galvanised steel for frame
Surface finish	Epoxy-polyester powder
Colour	Handle: black RAL 9005 Enclosure: grey RAL 7035

Environment

Standards	IEC 62208
Product certifications	BV DNV UL
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(Y Y W W)	0940

Contractual warranty

Period	18 months
--------	-----------