



Polyester glassreinf. plinth for encl. PLA(T)74 front opening IP44-IK10 RAL7035

NSYZA274G

١	V	1	а	ı	r

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth
Anwendung	Multi-purpose
Nennmaße des Gehäuses	-
Device composition	fixing elements 2 front panel 2 side part
Range compatibility	Thalassa (Thalassa PLA)

Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 mm
Width	744 mm
Depth	350 mm

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.0 cm
Package 1 Width	21.5 cm
Package 1 Length	77.5 cm
Package 1 Weight	6.61 kg

Offer Sustainability

Sustainable offer status Green Premium product

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)