
# Product datasheet Characteristics

# NSYZZ274G

Polyester glassreinf. plinth for encl. PLAZ(T)74 front opening IP44-IK10 RAL7035





#### Main

Range	Thalassa	
Accessory / separate part category	Enclosure accessory	ž
Product or component type	Plinth	9
Device application	Multi-purpose	
Enclosure nominal dimensions	- 420 mm	
Device composition	2 front panel Fixing elements 2 side part	vije.
Range compatibility	Thalassa PHD Thalassa PLA	A

### Complementary

Fixing mode	By screws - on side parts location	
Colour	Plinth : grey RAL 7035	
Height	200 mm	
Width	785 mm	
Depth	410 mm	

#### Environment

IP degree of protection	IP44	
ir degree or protection	11744	
IK degree of protection	IK10	}
IK degree of protection	INTO	•

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	Th
REACh	Reference not containing SVHC above the threshold	

### Reference not containing SVHC above the threshold

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
Contractual warranty	
Warranty period	18 months