



Main

Commercial Status	Commercialised
Range of product	PowerLogic PM800
Device short name	PM820
Product or component type	Power meter

Complementary

Power quality analysis	Up to the 31st harmonic
Type of measurement	Power factor (per phase) Energy Reactive power (per phase) Active power (per phase) Apparent power (per phase) Reactive power (total) Active power (total) Apparent power (total) Power factor (total) Frequency Voltage Current
Supply voltage	115...415 V AC (350...450 Hz) 115...415 V AC (45...67 Hz) 125...250 V DC
Network frequency	45...67 Hz 350...450 Hz
Power consumption in VA	15 VA
Display type	Backlit LCD
Display resolution	6 lines
Sampling rate	128 samples/cycle
Measurement current	5 A 1 A
Input type	Current 0.005...10 A (impedance <= 0.1 Ohm)
Measurement voltage	0...347 V AC phase to neutral 0...600 V AC phase to phase
Number of inputs	1 digital 0...5 mA 24...125 V AC/DC
Measurement accuracy	± 0.2 % power ± 0.002 power factor ± 0.01 Hz frequency ± 0.2 % energy ± 0.2 % voltage (10...227 V) ± 0.5 % current (0.5...10 A)
Accuracy class	Class 0.2 (active energy according to ANSI C12.20) Class 0.5S (active energy according to IEC 62053-22) Class 2 (reactive energy according to IEC 62053-23)
Number of outputs	1 digital (static)
Communication port protocol	Modbus: 38.4 kbauds,
Communication port support	RS485


The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Data recording	Alarms Event logs Min/Max of instantaneous values Time stamping GPS synchronisation Basic with 2 data logs
Memory capacity	80 kB

Environment

Electromagnetic compatibility	Limitation of voltage changes, voltage fluctuations and flicker in low-voltage, conforming to IEC 61000-3-3 Immunity to microbreaks and voltage drops class class III, conforming to IEC 61000-4-11 Immunity to impulse waves class class III, conforming to IEC 61000-4-8 Conducted RF disturbances class class III, conforming to IEC 61000-4-6 1.2/50 µs shock waves immunity test class class III, conforming to IEC 61000-4-5 Electrical fast transient/burst immunity test class class III, conforming to IEC 61000-4-4 Susceptibility to electromagnetic fields class class III, conforming to IEC 61000-4-3 Electrostatic discharge immunity test class class III, conforming to IEC 61000-4-2 Conducted and radiated emissions, conforming to EN 55011 class A Limits for harmonic current emissions, conforming to IEC 61000-3-2 Immunity to impulse waves, conforming to IEC 61000-4-12
Mounting mode	Flush-mounted
Mounting support	Panel
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	IP52 (front face) conforming to IEC 60529 IP30 (back) conforming to IEC 60529
Relative humidity	90 % 40 °C
Pollution degree	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	0...3000 m
Standards	IEC 61010-1 UL 508 CSA C22.2 No 14
Product certifications	CE CULus
Width	96 mm
Depth	70 mm (meter)
Height	96 mm
Product weight	0.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Product environmental profile	Available
Product end of life instructions	Available  Download End Of Life Manual