

**Monitoring and control (remote operation)**

**Circuit breaker accessories**

	Breaker Status Control Module	BSCM	LV434205
---	-------------------------------	------	----------







**ULP display module (1)**

	Switchboard front display module FDM121		TRV00121
	FDM mounting accessory (diameter 22 mm)		TRV00128



**ULP communication module**

	Modbus interface	Modbus SL communication interface module	TRV00210
---	------------------	--	----------


**ULP wiring accessories**

	NSX cord L = 0.35 m		LV434200
	NSX cord L = 1.3 m		LV434201
	NSX cord L = 3 m		LV434202
	NSX cord for U > 480 V AC L = 0.35 m		LV434204
	10 stacking connectors for communication interface modules		TRV00217
	10 Modbus line terminators		VW3A8306DRC (2)
	RS 485 roll cable (4 wires, length 60 m)		50965
	10 RJ45 connectors female/female		TRV00870
	10 ULP line terminators		TRV00880
	10 RJ45/RJ45 male cord L = 0.3 m		TRV00803
	10 RJ45/RJ45 male cord L = 0.6 m		TRV00806
	5 RJ45/RJ45 male cord L = 1 m		TRV00810
	5 RJ45/RJ45 male cord L = 2 m		TRV00820
	5 RJ45/RJ45 male cord L = 3 m		TRV00830
	1 RJ45/RJ45 male cord L = 5 m		TRV00850

**Power supply modules**

	External power supply module 100-240 V AC 110-230 V DC / 24 V DC-3 A class 2		ABL8RPS24030 (2)
	External power supply module 24 V DC-1 A OVC IV		
	24-30 V DC		54440
	48-60 V DC		54441
	100-125 V AC		54442
	110-130 V AC		54443
	200-240 V AC		54444
	380-415 V AC		54445

**Battery module**

	24 V DC battery module		54446
---	------------------------	--	-------

(1) For measurement display with Micrologic A and E or status display with BSCM.  
(2) See Telemecanique catalogue.