

Product datasheet

Specifications



Graphic Display Terminal - 240 x 160 pixels - IP65

VW3A1111

Main

Range of product	Altivar
Range compatibility	Altivar Process ATV900 Altivar Process ATV600 Altivar Machine ATV340
Accessory / separate part category	Display and signalling accessories
Accessory / separate part type	Display terminal
Accessory / separate part destination	Variable speed drive
Product specific application	To control, adjust and configure the drive To save and download configurations To display the current values
IP degree of protection	IP65

Complementary

Language	Spanish Romanian Turkish Polish Swedish Estonian Bulgarian English Russian Greek Danish Hungarian Chinese Norwegian Lituanien French Brazilian German Korean Portuguese Finnish Czech Slovak Taiwanese Dutch Italian
Realtime clock	Built-in
Battery size	CR2032
Battery life	10 year(s)
Display type	Backlit LCD screen white and red
Messages display capacity	8 lines

Pixel resolution	240 x 160
Net weight	0.2 kg

Environment

Ambient air temperature for operation	-15...50 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	264 g
Package 1 Height	5.7 cm
Package 1 width	13.7 cm
Package 1 Length	18.6 cm
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Weight	6.069 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------