

Main

Commercial Status	Commercialised
Product or component type	Communication card
Range compatibility	Altivar 312 Altivar 312 Solar
Communication port protocol	CANopen daisy chain
Electrical connection	2 connectors RJ45, CANopen 1 removable screw terminal block for inputs/outputs 1 connector RJ45, Modbus
Transmission rate	10, 20, 50, 125, 250, 500 kbps or 1 Mbps
Number of addresses	1...127

Complementary

Input/Output number	R2: 1 relay output LI1...LI3: 3 logic input AI2 and AI3: 2 analog input
Physical interface	RS485 multidrop serial link
Transmission frame	RTU
Communication service	1 receive SDO + 1 transmit SDO CiA 402 profile Communication monitoring node guarding and heartbeat PDO 1 : cannot be configured, asynchronous PDO 6 : can be configured, asynchronous, synchronous, cyclic asynchronous
Product weight	0.2 kg

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYWW)	0931

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.