



Main

Product or component type	Communication module
---------------------------	----------------------

Complementary

Range compatibility	Altivar 32 Altivar Process ATV600 Altivar Process ATV900
Communication port protocol	Profinet Link Layer Discovery Protocol
Electrical connection	2 connectors RJ45 Ethernet
Transmission rate	100 Mbits
Web server	Embedded HTTP server
Web services	Data editor Drive monitor Drive parameters Drive recorder Ethernet statistics IPar client settings Save/Restore drive configuration
Display type	1 LED for TX/RX (Transmit/Receive port 2) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for NS (Network Status) 1 LED for MS (Module Status)
Bus profile	PROFIdrive
Standards	IEC 61800-7-201 (CiA 402)
Product weight	0.3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.