

# Pendant control stations

Double insulated, type XAC B

Metal, type XAC M

For control or power circuits

Separate components and spare parts



ZA2 BS844



ZA2 BS944



ZA2 BD



ZA2 BG



ZA2 BB

## Operating heads for front or base mounting (1)

Description	Colour	Type	Reference	Weight kg
<b>Trigger action latching Emergency stop (2)</b>	Red	Ø 30 mm	ZA2 BS834	0.028
Turn to release (Emergency stop function)		Ø 40 mm	ZA2 BS844	0.033
<b>Trigger action latching Emergency stop (2) (3)</b>	Red	Ø 30 mm	ZA2 BS934	0.060
Key release (n° 455)		Ø 40 mm	ZA2 BS944	0.065
Key withdrawal in rest (unactuated) position (Emergency stop function)				
<b>Selector switches, standard handle (4)</b>	Black	2 position, stay put	ZA2 BD2	0.018
		3 position, stay put (5)	ZA2 BD3	0.018
<b>Key switches</b> (key n° 455) (3)	–	2 position, stay put	ZA2 BG4	0.042
Key withdrawal in left and right-hand positions		3 position, stay put (5)	ZA2 BG5	0.042
<b>Key switches</b> (key n° 455) (3)	–	2 position, stay put	ZA2 BG2	0.042
Key withdrawal in left-hand position				
<b>Key switches</b> (key n° 455) (3)	–	2 position	ZA2 BG6	0.042
Spring return from right to left				
Key withdrawal in left-hand position				
<b>Key switches</b> (key n° 455) (4) (3)	–	3 position, stay put (5)	ZA2 BG3	0.042
Key withdrawal in centre position				
<b>Wobblesticks (6)</b>	Black	–	ZA2 BB2	0.060
Operates in all directions for fast stop	Red	–	ZA2 BB4	0.060

## Operating head for isolating block

Description	Colour	Type	Reference	Weight kg
<b>Mushroom head, latching</b>	Red	Ø 40 mm	ZA2 BS14	0.065
Key release (n° 455)				
Key withdrawal in rest (unactuated) position (Emergency stop function)				

## Pilot light heads

Description	Colour	Reference	Weight kg
<b>For use with incandescent bulbs</b>			
<b>Lens cap with fixing bezel</b>	White	ZA2 BV01	0.015
	Green	ZA2 BV03	0.015
	Red	ZA2 BV04	0.015
	Yellow	ZA2 BV05	0.015
	Blue	ZA2 BV06	0.015
	Clear	ZA2 BV07	0.015
<b>For use with neon bulbs</b>			
<b>Lens cap with fixing bezel</b>	Green	ZA2 BV033	0.015
	Red	ZA2 BV043	0.015
	Yellow	ZA2 BV053	0.015
	Clear	ZA2 BV073	0.015

(1) The technical characteristics of pendant control stations XAC B and XAC M can only be guaranteed by using the operating heads ZA2 B●● listed above.

(2) Trigger action mechanically latching Emergency stop pushbuttons conform to standards EN/IEC 60204-32, EN/ISO 13850, Machinery directive 98/37/EC and standard EN/IEC 60947-5-5.

(3) Other key numbers available on request, please consult your Customer Care Centre.

(4) Selector switches or key switches with other mechanical functions: please consult your Customer Care Centre.

(5) Only suitable for front mounting.

(6) Base mounting recommended.



ZA2 BV0