



FUSE LINK CLASS CC ACC. TO UL STANDARD 248-4
SLOW-BLOW RATED CURRENT 8 A RATED VOLTAGE
UP TO 600 V AC SIZE 10.3 MM X 38.1 MM

Similar to image

Technical data:

product brand name		SETRON
Product designation		Fuse systems
Operating current / rated value	A	8
Operating class of the fuse link		CC
Tripping characteristic class		Time-lag
Size of the fallback-system / acc. to DIN EN 60269-1		others
Operating voltage / rated value	V	600
Breaking capacity maximum short-circuit current (I _{cu}) / with AC / rated value	kA	200
Color coding of the fuse link		others
Item designation		
<ul style="list-style-type: none"> • according to DIN EN 61346-2 • according to DIN EN 81346-2 		F F

Certificates/approvals:

General Product Approval



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NW1080-0HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NW1080-0HG/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW1080-0HG

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

Datanorm [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)



last change:

Apr 21, 2014