

CONTACTOR RELAY, 4NO, AC 230 V, 50 HZ,
SCREW CONNECTION, SIZE S00



General details:		
Product brand name		SIRIUS
Product designation		contactor relay
Size of the contactor		S00
Protection class IP / frontal/front side		IP20
Degree of pollution		3
Insulation voltage / with degree of pollution 3 / rated value	V	690
Altitude of installation site / at a height over sea level / maximum	m	2,000
Ambient temperature		
• during transport	°C	-55 ... 80
• during storage	°C	-55 ... 80
• during the operating phase	°C	-25 ... 60
Resistance against shock		10g / 5 ms and 5g / 10 ms
Impulse voltage resistance / rated value	kV	6
Item designation		
• according to DIN EN 61346-2		K
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		K
Mechanical operating cycles as operating time		
• of the contactor / typical		30,000,000

- of the contactor with added auxiliary switch block / typical
- of the contactor with added electronics-compatible auxiliary switch block / typical

10,000,000

5,000,000

Control circuit:

Type of voltage / of the controlled supply voltage		AC
control supply voltage frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Control supply voltage / 1		
• at 50 Hz		
• for AC / rated value	V	230
• at 60 Hz		
• for AC / rated value	V	230
Operating range factor control supply voltage rated value / of the solenoid		
• at 50 Hz		
• for AC		0.8 ... 1.1
• at 60 Hz		
• for AC		0.85 ... 1.1
Apparent pull-in power / of the solenoid / for AC	V·A	27
Apparent holding power / of the solenoid / for AC	V·A	4.6
Power factor inductive		
• at pull-in power of the coil		0.8
• at holding power of the coil		0.27
Resistive loss der Magnetspule bei DC typisch		-

Auxiliary circuit:

Product extension / auxiliary switch		Yes
Identification number and letter for switching elements		40 E
Contact reliability / of the auxiliary contacts		1 faulty switching per 100 million (17 V, 1 mA)
Number of NC contacts / for auxiliary contact		0
• delayed switching		0
• instantaneous switching		0
• asynchronous switching		0
• lagging switching		0
Number of NO contacts / for auxiliary contact		4
• instantaneous switching		4
• delayed switching		0
• asynchronous switching		0
• leading switching		0

Number of changeover contacts		
• for auxiliary contact		0
• of the auxiliary contacts / non-delayed		0
Operating current / of the auxiliary contacts		
• at AC-12 / maximum	A	10
• at AC-15		
• at 230 V	A	6
• at 400 V	A	3
• at 500 V	A	2
• at 690 V	A	1
• with 1 current path		
• at DC-12		
• at 24 V	A	10
• at 110 V	A	3
• at 220 V	A	1
• at DC-13		
• at 24 V	A	10
• at 110 V	A	4
• at 220 V	A	0.22

Short-circuit:

Design of the fuse link / for short-circuit protection of the auxiliary switch / required

fuse gL/gG: 10 A

Installation/mounting/dimensions:

built in orientation		with vertical mounting surface +/-180° rotatable, with vertical mounting surface +/- 30° tiltable to the front and back
Type of fixing/fixation		screw and snap-on mounting
Width	mm	45
Height	mm	57.5
Depth	mm	72
distance, to be maintained, to the ranks assembly / sideways	mm	0

Connections:

design of the electrical connection / for auxiliary and control current circuit

screw-type terminals

Type of connectable conductor cross section

• for auxiliary contacts

• solid

2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), max. 2x (1 ... 4 mm²)

• finely stranded

• with wire end processing

2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)

• for AWG conductors / for auxiliary contacts

2x (20 ... 16), 2x (18 ... 14), 1x 12

Certificates/approvals:

verification of suitability

CSA / UL / CCC / GL / LRS / BV / DNV / RMRS / RINA

Safety:

Proportion of dangerous failures

- with high demand rate / according to SN 31920
- with low demand rate / according to SN 31920

% 75
% 40

T1 value / for proof test interval or service life / according to IEC 61508

a 20

Protection against electrical shock

finger-safe

B10 value / with high demand rate / according to SN 31920

1,000,000

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Global Industry Mall (Online ordering system)


<http://www.siemens.com/industrial-controls/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)






<http://support.automation.siemens.com/WW/view/en/3RH1140-1AP00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RH1140-1AP00



-K



last change:

Jun 14, 2010