



THERMISTOR MOTOR PROTECTION MULTIFUNCTION
EVALUATION UNIT MANUAL/AUTO/REMOTE,
SHORT-CIRC.DETECT., 2W, UC 24...240V,
SCREW CONNECTION

General technical details:



| | | |
|---|----|-------|
| type of voltage | | AC/DC |
| Supply voltage frequency | | |
| <ul style="list-style-type: none"> • 1 / for auxiliary and control current circuit • rated value | Hz | 50 |
| <ul style="list-style-type: none"> • 2 / for auxiliary and control current circuit • rated value | Hz | 60 |
| Control supply voltage | | |
| <ul style="list-style-type: none"> • 1 • at 50 Hz / for AC <ul style="list-style-type: none"> • initial rated value • final rated value • at 60 Hz / for AC <ul style="list-style-type: none"> • initial rated value • final rated value • for DC <ul style="list-style-type: none"> • initial rated value • final rated value | V | 24 |
| | V | 240 |
| | V | 24 |
| | V | 240 |
| | V | 24 |
| | V | 240 |
| Number of measuring circuits | | 1 |
| Number of NC contacts / for auxiliary contacts | | 0 |

| | | |
|---|----|------------|
| Number of NO contacts / for auxiliary contacts | | 0 |
| Number of change-over switches / for auxiliary contacts | | 2 |
| Measurable temperature | | |
| • initial value | °C | 60 |
| • final value | °C | 180 |
| Product function | | |
| • reclosing interlock | | Yes |
| • self-reset | | Yes |
| • defect storage | | Yes |
| • reset external | | Yes |
| Item designation / according to DIN EN 61346-2 | | K |
| Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 | | K |
| Ambient temperature / during operating phase | °C | -25 ... 60 |

Mechanical design:

| | | |
|---|----|----------------------|
| Design of the electrical connection / for auxiliary and control current circuit | | screw-type terminals |
| Design of the electrical connection / jumper socket | | No |
| Type of display / LED | | Yes |
| Protection class IP | | IP20 |
| Width | mm | 22.5 |
| Height | mm | 102 |
| Depth | mm | 91 |

Certificates/approvals:


| General Product Approval | For use in hazardous locations | Test Certificates |
|---|---|--|
| CQC  ROSTEST | PTB | Manufacturer |
| Shipping Approval | PRS  | other Manufacturer |

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator
<http://www.siemens.com/cax>



last change:

Jun 13, 2011