

Fan for SIRIUS soft starter 3RW403 S2, 3RW404 S3



product brand name	SIRIUS
product category	Fan
product designation	Fan
Substance Prohibitance (Date)	05/01/2012
Installation/ mounting/ dimensions	
height	40 mm
width	40 mm
depth	10 mm
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Approvals Certificates	
General Product Approval	EMV



[Confirmation](#)



EMV	Test Certificates	Marine / Shipping	other
KC	Special Test Certificate	 DNV	 LRS
		 PRS	Confirmation

Further information

- Information on the packaging <https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...) <https://www.siemens.com/ic10>
- Industry Mall (Online ordering system) <https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4947-8VB00>
- Cax online generator <http://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=3RW4947-8VB00>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...) <https://support.industry.siemens.com/cs/ww/en/ps/3RW4947-8VB00>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4947-8VB00&lang=en
- Characteristic: Tripping characteristics, I_t, Let-through current <https://support.industry.siemens.com/cs/ww/en/ps/3RW4947-8VB00/char>
- Characteristic: Installation altitude <http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4947-8VB00&objecttype=14&gridview=view1>
- Simulation Tool for Soft Starters (STS)

last modified:

12/15/2020 

