

22MM PLASTIC ROUND COMPLETE UNIT
COMBINATION: DRIVE FOR POTENTIOMETER 30...32MM
LONG, ACC. TO DIN41 450



Actuator:		
Design of the operating mechanism		rotary switch
Shape / of the actuating element		round
Manner of function / of the actuating element		
<ul style="list-style-type: none"> • Latching • momentary contact type 		No Yes
Material / of the actuating element		plastic
Button:		
Design of the button		raised
Color / of the button		black
Front ring:		
Product component / front ring		Yes
Material / of the front ring		plastic
Color / of the front ring		black
General technical details:		
Product expansion / optional / Light source		No
Vibration resistance / acc. to IEC 60068-2-6		20 ... 200 Hz: 5g
Shock resistance / for devices without incandescent lamp / acc. to IEC 60068-2-27		<= 50g

Reference code		
• acc. to DIN EN 61346-2		S
• acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		S




Installation/mounting/dimensions:

Mounting type		front mounting
Material / of the enclosure		plastic
Outer diameter / of the actuating element	mm	15
Shape / of the installation opening		round
Installation width	mm	30
Mounting diameter	mm	22
Mounting height	mm	25
Height	mm	30
Width	mm	30
Depth	mm	44

Ambient conditions:

Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +70
Protection class IP		IP65
Climate class / acc. to DIN EN ISO 6270-2		KTW24

Certificates/approvals:

General Product Approval	Declaration of Conformity	Test Certificates
 	 EG-Konf.	Special Test Certificate
other		
Confirmation	other	Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall
CAX-Online-Generator http://www.siemens.com/cax
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3SB1000-7CH07/all

last change:

Nov 3, 2014