SIEMENS

Product data sheet

3SB3001-6AA30

22MM PLASTIC ROUND INDICATOR: INDICATOR LIGHT WITH SMOOTH LENSE ILLUMINABLE WITH HOLDER YELLOW

Actuator:		
Design of the product		Single device round
Design of the operating mechanism		indicator light
Color / of the actuating element		Yellow
Material / of the actuating element		plastic
Shape / of the actuating element		Smooth lens
Number of switching positions		0
Product component / front ring		No
Product function / EMERGENCY STOP function		No
Holder:		
Material / of the holder		Plastic
General technical data:		
Shock resistance		
• for devices with incandescent lamp / acc. to IEC 60068-2-27		<= 30g
• for devices without incandescent lamp / acc. to IEC 60068-2-27		<= 50g
Vibration resistance / acc. to IEC 60068-2-6		20 200 Hz: 5g
Reference code		
• acc. to DIN EN 61346-2		Ρ
acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		н
Tightening torque / of the screws in the bracket / maximum	N∙m	1
Ambient temperature		
during operation	°C	-25 +70
during storage	°C	-40 +80
Protection class IP		IP66
Climate class / during operation / acc. to EN 60721		3К6
Mounting type		front mounting
Shape / of the installation opening		round
Installation width	mm	28
Mounting diameter	mm	22
Mounting height	mm	11

nstallation depth			mm 29		
Certificates/ app	provals:				
General Product	Approval		Declaration of Conformity	Test Certificates	
(SA) CSA	EAC		EG-Konf.	Special Test Certificate	
Shipping Approv	/al				
ABS	DNV DNV	Lloyd's Kegister	PRS	RINA	
other					
Confirmation	other	Environmental Confirmations			
Further informa	tion:				
	Downloadcenter (Cat s.com/industrial-contro	alogs, Brochures,)			
	ine ordering system				
Cax online genera http://www.siemens					
		es, Characteristics, FAQs, VW/view/en/3SB3001-6AA3	-		
mage database (p	product images, 2D o	limension drawings, 3D m	nodels, device circu	it diagrams,)	

last change:

Jun 16, 2014