



22MM PLASTIC ROUND INDICATOR: INDICATOR LIGHT WITH SMOOTH LENSE ILLUMINABLE WITH HOLDER WHITE

Actuator:	
Design of the product	Single device round
Design of the operating mechanism	indicator light
Color / of the actuating element	White
Material / of the actuating element	plastic
Shape / of the actuating element	Smooth lens
Number of switching positions	0
Product component / front ring	No
Product function / EMERGENCY STOP function	No

Holder:	
Material / of the holder	Plastic

General technical data:	
Shock resistance	
<ul style="list-style-type: none"> for devices with incandescent lamp / acc. to IEC 60068-2-27 for devices without incandescent lamp / acc. to IEC 60068-2-27 	<p><= 30g</p> <p><= 50g</p>
Vibration resistance / acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Reference code	
<ul style="list-style-type: none"> acc. to DIN EN 61346-2 	P

• acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		H
Tightening torque / of the screws in the bracket / maximum	N-m	1
Ambient temperature		
• during operation	°C	-25 ... +70
• during storage	°C	-40 ... +80
Protection class IP		IP66
Climate class / during operation / acc. to EN 60721		3K6
Mounting type		front mounting
Shape / of the installation opening		round
Installation width	mm	28
Mounting diameter	mm	22
Mounting height	mm	11
Installation depth	mm	29

Certificates/ approvals:

General Product Approval



[Special Test Certificate](#)

EG-Konf.

Shipping Approval



ABS

DNV

LRS

PRS

RINA

other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3SB3001-6AA60/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3001-6AA60

last change:

Jun 16, 2014