



Digital monitoring relay Voltage monitoring, 22.5 mm from 10 to 600 V AC/DC Overshoot and undershoot 24 to 240 V AC/DC 50 to 60 Hz DC and AC Noise pulses delay 0.1 to 20 s Hysteresis 0.1 to 300 V 1 change-over contact with or without fault buffer screw terminal Successor product for 3UG3532-1AL20, 3UG3532-1AG20

product brand name	SIRIUS																						
product designation	Voltage monitoring relay with digital setting																						
product type designation	3UG4																						
General technical data																							
product function	Voltage monitoring relay																						
design of the display	LCD																						
insulation voltage for overvoltage category III according to IEC 60664	690 V																						
<ul style="list-style-type: none"> with degree of pollution 3 rated value 																							
type of voltage	AC/DC																						
<ul style="list-style-type: none"> for monitoring of the control supply voltage 																							
surge voltage resistance rated value	4 kV																						
maximum permissible voltage for safe isolation	300 V																						
<ul style="list-style-type: none"> between auxiliary and auxiliary circuit between control and auxiliary circuit 																							
protection class IP	IP20																						
shock resistance according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms																						
vibration resistance according to IEC 60068-2-6	1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g																						
mechanical service life (switching cycles) typical	10 000 000																						
electrical endurance (switching cycles) at AC-15 at 230 V typical	100 000																						
thermal current of the switching element with contacts maximum	5 A																						
reference code according to IEC 81346-2	K																						
relative repeat accuracy	1 %																						
Substance Prohibitance (Date)	05/01/2012																						
Product Function																							
product function	<table border="0"> <tr><td>• undervoltage detection</td><td>Yes</td></tr> <tr><td>• overvoltage detection</td><td>Yes</td></tr> <tr><td>• overvoltage detection 1 phase</td><td>Yes</td></tr> <tr><td>• overvoltage detection 3 phase</td><td>No</td></tr> <tr><td>• overvoltage detection DC</td><td>Yes</td></tr> <tr><td>• undervoltage detection 1 phase</td><td>Yes</td></tr> <tr><td>• undervoltage detection 3 phases</td><td>No</td></tr> <tr><td>• undervoltage detection DC</td><td>Yes</td></tr> <tr><td>• voltage window recognition 1 phase</td><td>Yes</td></tr> <tr><td>• voltage window recognition 3 phase</td><td>No</td></tr> <tr><td>• voltage window recognition DC</td><td>Yes</td></tr> </table>	• undervoltage detection	Yes	• overvoltage detection	Yes	• overvoltage detection 1 phase	Yes	• overvoltage detection 3 phase	No	• overvoltage detection DC	Yes	• undervoltage detection 1 phase	Yes	• undervoltage detection 3 phases	No	• undervoltage detection DC	Yes	• voltage window recognition 1 phase	Yes	• voltage window recognition 3 phase	No	• voltage window recognition DC	Yes
• undervoltage detection		Yes																					
• overvoltage detection		Yes																					
• overvoltage detection 1 phase		Yes																					
• overvoltage detection 3 phase		No																					
• overvoltage detection DC		Yes																					
• undervoltage detection 1 phase		Yes																					
• undervoltage detection 3 phases		No																					
• undervoltage detection DC		Yes																					
• voltage window recognition 1 phase		Yes																					
• voltage window recognition 3 phase		No																					
• voltage window recognition DC		Yes																					
• undervoltage detection																							
• overvoltage detection																							
• overvoltage detection 1 phase																							
• overvoltage detection 3 phase																							
• overvoltage detection DC																							
• undervoltage detection 1 phase																							
• undervoltage detection 3 phases																							
• undervoltage detection DC																							
• voltage window recognition 1 phase																							
• voltage window recognition 3 phase																							
• voltage window recognition DC																							

<ul style="list-style-type: none"> adjustable open/closed-circuit current principle 	Yes
<ul style="list-style-type: none"> external reset 	Yes
<ul style="list-style-type: none"> auto-RESET 	Yes
Control circuit/ Control	
control supply voltage at AC	
<ul style="list-style-type: none"> at 50 Hz rated value 	24 ... 240 V
<ul style="list-style-type: none"> at 60 Hz rated value 	24 ... 240 V
control supply voltage at DC	
<ul style="list-style-type: none"> rated value 	24 ... 240 V
operating range factor control supply voltage rated value at DC	
<ul style="list-style-type: none"> initial value 	0.85
<ul style="list-style-type: none"> full-scale value 	1.1
operating range factor control supply voltage rated value at AC at 50 Hz	
<ul style="list-style-type: none"> initial value 	0.85
<ul style="list-style-type: none"> full-scale value 	1.1
operating range factor control supply voltage rated value at AC at 60 Hz	
<ul style="list-style-type: none"> initial value 	0.85
<ul style="list-style-type: none"> full-scale value 	1.1
Measuring circuit	
measurable line frequency	40 ... 500 Hz
measurable voltage at AC	600 ... 10 V
measurable voltage at DC	10 ... 600 V
adjustable response delay time	
<ul style="list-style-type: none"> with lower or upper limit violation 	0.1 ... 20 s
accuracy of digital display	+/-1 digit
relative temperature-related measurement deviation	0.1 %
Precision	
relative metering precision	5 %
Auxiliary circuit	
number of NC contacts delayed switching	0
number of NO contacts delayed switching	0
number of CO contacts delayed switching	1
operating frequency with 3RT2 contactor maximum	5 000 1/h
Main circuit	
number of poles for main current circuit	1
operational current at 17 V minimum	5 mA
continuous current of the DIAZED fuse link of the output relay	4 A
Electromagnetic compatibility	
conducted interference	
<ul style="list-style-type: none"> due to burst according to IEC 61000-4-4 	2 kV
<ul style="list-style-type: none"> due to conductor-earth surge according to IEC 61000-4-5 	2 kV
<ul style="list-style-type: none"> due to conductor-conductor surge according to IEC 61000-4-5 	1 kV
field-based interference according to IEC 61000-4-3	10 V/m
electrostatic discharge according to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge
Galvanic isolation	
design of the electrical isolation	Protective separation
galvanic isolation	
<ul style="list-style-type: none"> between input and output 	Yes
<ul style="list-style-type: none"> between the outputs 	Yes
<ul style="list-style-type: none"> between the voltage supply and other circuits 	Yes
Connections/ Terminals	
product component removable terminal for auxiliary and control circuit	Yes
type of electrical connection	screw-type terminals
type of connectable conductor cross-sections	

<ul style="list-style-type: none"> • solid • finely stranded with core end processing • at AWG cables solid • at AWG cables stranded 	1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²) 2x (20 ... 14) 2x (20 ... 14)
connectable conductor cross-section	
<ul style="list-style-type: none"> • solid • finely stranded with core end processing 	0.5 ... 4 mm ² 0.5 ... 2.5 mm ²
AWG number as coded connectable conductor cross section	
<ul style="list-style-type: none"> • solid • stranded 	20 ... 14 20 ... 14
tightening torque with screw-type terminals	1.2 ... 0.8 N·m

Installation/ mounting/ dimensions

mounting position	any
fastening method	snap-on mounting
height	92 mm
width	22.5 mm
depth	91 mm
required spacing	
<ul style="list-style-type: none"> • with side-by-side mounting <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side • for grounded parts <ul style="list-style-type: none"> — forwards — backwards — upwards — at the side — downwards • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — at the side 	0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm

Ambient conditions

installation altitude at height above sea level maximum	2 000 m
ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	-25 ... +60 °C -40 ... +85 °C -40 ... +85 °C

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity
---------------------------------	------------	----------------------------------

[Confirmation](#)



Test Certificates	Marine / Shipping	other	Railway
--------------------------	--------------------------	--------------	----------------

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



[Confirmation](#)

[Vibration and Shock](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4632-1AW30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4632-1AW30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UG4632-1AW30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UG4632-1AW30&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3UG4632-1AW30/manual>

last modified:

11/17/2021 