

CIRCUIT-BREAKER VL 250N STANDARD BREAKING CAPACITY ICU=55KA / 415 V AC 3 POLE, LINE PROTECTION OVERCURRENT RELEASE TM, LI IN=250A, RATED CURRENT IR=200-250A, OVERLOAD II=1200-2500A, SHORT-CIRCUIT WITH BOX TERMINAL

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		TM
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL3
Electrical endurance (switching cycles) / typical		10 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	120
Voltage		
Rated operational voltage $U_e$ / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
--	----	---

### Protection class

<b>Protection class IP</b>		IP20
<b>Protective function of the overcurrent release</b>		LI

### Electricity

Continuous current / rated value	A	250
Derating temperature / for the rated value of the continuous current	°C	50
<b>Adjustable response value current</b>		
• of the current-dependent overload release / Full-scale value	A	250
• of the instantaneous short-circuit release / initial value	A	1 250
• of the instantaneous short-circuit release / Full-scale value	A	2 500

### Main circuit

<b>Operating frequency</b>		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
<b>Operating voltage</b>		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
<b>Operating current</b>		
• at 40 °C / rated value	A	250
• at 50 °C / rated value	A	250
• at 55 °C / rated value	A	232.5
• at 60 °C / rated value	A	232.5
• at 65 °C / rated value	A	215
• at 70 °C / rated value	A	215

### Auxiliary circuit

Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0

### Suitability

<b>Suitability for use</b>		system protection
----------------------------	--	-------------------

### Adjustable parameters

<b>Adjustable response value current / of the current-dependent overload release / initial value</b>	A	200
--	---	-----

## Product details

<b>Product component</b>		
• Trip indicator		No
• Auxiliary switch		No
• Voltage trigger		No
• undervoltage release		Yes
• undervoltage release with leading contact		No
Product expansion / optional / motor drive		Yes

## Product function

<b>Product function</b>		
• of the thermal overload release		adjustable
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		Yes

## Short circuit

<b>Operational short-circuit current breaking capacity (Ics)</b>		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	20
• at 690 V / rated value	kA	6
<b>Maximum short-circuit current breaking capacity (Icu)</b>		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 440 V / rated value	kA	25
• at 480 V / acc. to NEMA / rated value	kA	25
• at 500 V / rated value	kA	25
• at 600 V / acc. to NEMA / rated value	kA	12
• at 690 V / rated value	kA	12

## Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of connectable conductor cross-sections		
• for main contacts		
— with flexible busbar		17 x 10 mm
— solid		25 ... 185 mm <sup>2</sup>
— finely stranded / with core end processing		25 ... 120 mm <sup>2</sup>
— stranded		25 ... 185 mm <sup>2</sup>
• for auxiliary contacts		
— solid		0.75 ... 1.5 mm <sup>2</sup>

— finely stranded / with core end processing		0,75 ... 1.0 mm <sup>2</sup>
Type of electrical connection / for main current circuit		box terminals

### Mechanical Design

Height	mm	185.5
Width	mm	104.5
Depth	mm	106.5
Mounting type		fixed mounting

### Environmental conditions




<b>Ambient temperature</b>		
• during operation / minimum	°C	0
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

### Certificates

<b>Certificate of suitability</b>		IEC, standard switching capacity (N)
<b>Equipment marking</b>		Q
• acc. to DIN EN 61346-2		

<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>
 <a href="#">sonstig</a>	 <a href="#">TSE</a>	  EG-Konf.

<b>Test Certificates</b>	<b>Shipping Approval</b>				
<a href="#">spezielle Prüfbescheinigung</a> <a href="#">n</a>	 ABS	 BUREAU VERITAS	 DNV	 GL	 LRS

<b>Shipping Approval</b>	<b>other</b>				
 PRS	 RINA	 RMRS	<a href="#">sonstig</a>	<a href="#">Umweltbestätigung</a>	<a href="#">Bestätigungen</a>

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**  
<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL37251DC332HA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3VL37251DC332HA0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL37251DC332HA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL37251DC332HA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>

**last modified:**

28.12.2015