

CIRCUIT-BREAKER VL 800H HIGH SWITCHING
CAPACITY ICU=70KA / 415 V AC 3 POLE, LINE
PROTECTION OVERCURRENT RELEASE ETU10, LI
IN=800A, RATED CURRENT IR=320-800A,
OVERLOAD II=1,25TO8XIN, SHORT-CIRCUIT

Certificates

General Product Approval	EMC
--------------------------	-----



[sonstig](#)



[TSE](#)



Declaration of Conformity	Test Certificates	Shipping Approval
---------------------------	-------------------	-------------------



EG-Konf.

[spezielle Prüfbescheinigung](#)
[n](#)



DNV



GL



RINA



RMRS

other

[Bestätigungen](#)

[Umweltbestätigung](#)

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL67802AB360AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL67802AB360AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL67802AB360AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

25.01.2016