



CIRCUIT-BREAKER VL 800H HIGH BREAKING CAPACITY ICU=70KA / 415 V AC 3 POLE, LINE PROTECTION ELECTRONIC TRIP UNIT ETU10, LI IN=800A, RATED CURRENT IR=320-800A, OVERLOAD II=1,25TO8XIN, SHORT-CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU10
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL6
Electrical endurance (switching cycles) / typical		3 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		10 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	60
Voltage		
Rated operational voltage $U_e$ / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
<b>Protection class</b>		
Protection class IP		IP20
Protective function of the overcurrent release		LI
<b>Dissipation</b>		
Power loss [W]		
• maximum	W	250
<b>Electricity</b>		
Continuous current / rated value	A	800
Derating temperature / for the rated value of the continuous current	°C	50
<b>Adjustable response value current</b>		
• of the current-dependent overload release / Full-scale value	A	800
• of the instantaneous short-circuit release / initial value	A	1 000
• of the instantaneous short-circuit release / Full-scale value	A	6 400
<b>Main circuit</b>		
<b>Operating frequency</b>		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
<b>Operating voltage</b>		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
<b>Operating current</b>		
• at 40 °C / rated value	A	800
• at 50 °C / rated value	A	800
• at 55 °C / rated value	A	760
• at 60 °C / rated value	A	760
• at 65 °C / rated value	A	640
• at 70 °C / rated value	A	640
<b>Auxiliary circuit</b>		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		2
Number of NO contacts / for auxiliary contacts		2
<b>Suitability</b>		
Suitability for use		system protection

## Adjustable parameters

<b>Adjustable response value current / of the current-dependent overload release / initial value</b>	A	320
--	---	-----

## Product details

<b>Product component</b>		
• Trip indicator		No
• Auxiliary switch		Yes
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
<b>Product expansion / optional / motor drive</b>		Yes

## Product function

<b>Product function</b>		
• of the thermal overload release		adjustable
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		Yes

## Short circuit

<b>Operational short-circuit current breaking capacity (Ics)</b>		
• at 240 V / rated value	kA	75
• at 415 V / rated value	kA	70
• at 500 V / rated value	kA	30
• at 690 V / rated value	kA	10
<b>Maximum short-circuit current breaking capacity (Icu)</b>		
• at 240 V / rated value	kA	100
• at 415 V / rated value	kA	70
• at 440 V / rated value	kA	50
• at 480 V / acc. to NEMA / rated value	kA	50
• at 500 V / rated value	kA	40
• at 600 V / acc. to NEMA / rated value	kA	30
• at 690 V / rated value	kA	20

## Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of connectable conductor cross-sections		
• for auxiliary contacts		
— solid		0.75 ... 1.5 mm <sup>2</sup>
— finely stranded / with core end processing		0,75 ... 1.0 mm <sup>2</sup>
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design		
Height	mm	406.5
Width	mm	190
Depth	mm	176.5
Mounting type		fixed mounting

Environmental conditions		
<b>Ambient temperature</b>		
• during operation / minimum	°C	-25
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

Certificates		
<b>Certificate of suitability</b>		IEC, high switching capacity (H)
<b>Equipment marking</b>		Q
• acc. to DIN EN 61346-2		

General Product Approval	EMC
 CCC  CSA <a href="#">sonstig</a>	 EAC <a href="#">TSE</a>  C-TICK

Declaration of Conformity	Test Certificates	Shipping Approval			
 EG-Konf.	<a href="#">spezielle Prüfbescheinigung</a> <a href="#">n</a>	 DNV	 GL	 RINA	 RMRS

other
<a href="#">sonstig</a> <a href="#">Bestätigungen</a> <a href="#">Umweltbestätigung</a>

Further information
<b>Information- and Downloadcenter (Catalogs, Brochures,...)</b> <a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a>
<b>Industry Mall (Online ordering system)</b> <a href="https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL67802SB360AC1">https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL67802SB360AC1</a>
<b>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)</b> <a href="http://support.automation.siemens.com/WW/view/en/3VL67802SB360AC1/all">http://support.automation.siemens.com/WW/view/en/3VL67802SB360AC1/all</a>
<b>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)</b> <a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL67802SB360AC1">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL67802SB360AC1</a>

**CAX-Online-Generator**  
<http://www.siemens.com/cax>

**Tender specifications**  
<http://ausschreibungstexte.siemens.com/tiplv>

**last modified:**

28.12.2015