

CIRCUIT-BREAKER VL 1250N STANDARD
SWITCHING CAPACITY ICU=55KA / 415 V AC 4
POLE, LINE PROTECTION OVERCURRENT
RELEASE ETU20, LSI IN=1250A, RATED CURRENT
IR=500-1250A, OVERLOAD ISD=1,5TO9XIR, II=10XIN
SHORT-CIRCUIT N PROTECTED

Certificates

General Product Approval	EMC
--------------------------	-----



[sonstig](#)



[TSE](#)



Declaration of Conformity	Test Certificates	Shipping Approval
---------------------------	-------------------	-------------------



[spezielle Prüfbescheinigung](#)
[n](#)



Shipping Approval	other
-------------------	-------



[sonstig](#)

[Bestätigungen](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL77121BF460AC1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL77121BF460AC1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL77121BF460AC1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

25.01.2016