

CIRCUIT-BREAKER VL 1250H HIGH BREAKING CAPACITY ICU=70KA / 415 V AC 3 POLE, NON-AUTOMATIC OVERCURRENT RELEASE MAGNETIC IN=1250A, RATED CURRENT II=12000A, SHORT-CIRCUIT II=12000A, SHORT-CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		M
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL7
Electrical endurance (switching cycles) / typical		1 500
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		3 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	30
Voltage		
Rated operational voltage U_e / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
--	----	---

Protection class

Protection class IP		IP20
Protective function of the overcurrent release		I

Dissipation

Power loss [W]		
• maximum	W	210

Electricity

Continuous current / rated value	A	1 250
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable response value current		
• of the instantaneous short-circuit release / initial value	A	12 000
• of the instantaneous short-circuit release / Full-scale value	A	12 000

Main circuit

Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
Operating current		
• at 40 °C / rated value	A	1 250
• at 50 °C / rated value	A	1 250
• at 55 °C / rated value	A	1 162
• at 60 °C / rated value	A	1 162
• at 65 °C / rated value	A	1 075
• at 70 °C / rated value	A	1 075

Auxiliary circuit

Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0

Suitability

Suitability for use		non-automatic circuit-breakers
----------------------------	--	--------------------------------

Product details

Product component		
• Trip indicator		No
• Auxiliary switch		No
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
Product expansion / optional / motor drive		Yes

Product function

Product function		
• of the thermal overload release		without
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		No

Short circuit

Operational short-circuit current breaking capacity (Ics)		
• at 240 V / rated value	kA	50
• at 415 V / rated value	kA	35
• at 500 V / rated value	kA	30
• at 690 V / rated value	kA	15
Maximum short-circuit current breaking capacity (Icu)		
• at 240 V / rated value	kA	100
• at 415 V / rated value	kA	70
• at 440 V / rated value	kA	50
• at 480 V / acc. to NEMA / rated value	kA	50
• at 500 V / rated value	kA	40
• at 600 V / acc. to NEMA / rated value	kA	30
• at 690 V / rated value	kA	30

Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of connectable conductor cross-sections		
• for auxiliary contacts		
— solid		0.75 ... 1.5 mm ²
— finely stranded / with core end processing		0,75 ... 1.0 mm ²
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design

Height	mm	406.5
Width	mm	228.5
Depth	mm	333.5

Mounting type	fixed mounting
---------------	----------------

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	0
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80






Certificates

Certificate of suitability	IEC, high switching capacity (H)
Equipment marking	Q
• acc. to DIN EN 61346-2	




General Product Approval

 CCC	 CSA	sonstig	 EAC	TSE	 C-TICK
--	--	-------------------------	--	---------------------	---

Declaration of Conformity	Test Certificates	Shipping Approval
---------------------------	-------------------	-------------------

 EG-Konf.	spezielle Prüfbescheinigung n	 BUREAU VERITAS	 DNV	 GL	 LRS
---	--	--	---	---	--

Shipping Approval	other
-------------------	-------

 PRS	 RINA	 RMRS	Bestätigungen	Umweltbestätigung	sonstig
--	---	---	-------------------------------	-----------------------------------	-------------------------

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)**
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)**
<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL77122DE360AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<http://support.automation.siemens.com/WW/view/en/3VL77122DE360AA0/all>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL77122DE360AA0
- CAX-Online-Generator**
<http://www.siemens.com/cax>
- Tender specifications**
<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

28.12.2015