



NEOZED fuse-link, D02, 50 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

Model		
product brand name	SETRON	
product designation	NEOZED fuse link	
design of the product	SILIZED	
General technical data		
size of fuse system / acc. to DIN EN 60269-1	D02	
operating class of the fuse link	gR	
Supply voltage		
supply voltage		
• at DC	250 V	
operating voltage / rated value	400 V	
Dissipation		
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	12 W	
Main circuit		
operational current / rated value	50 A	
Appearance		
color coding of the fuse link	White	
breaking capacity maximum short-circuit current (I _{cu}) / at AC / rated value	50 kA	
Mechanical Design		
net weight	14 g	
ambient temperature / during operation		
• minimum	40 °C	
• maximum	40 °C	
General Product Approval	Declaration of Conformity	other



[Environmental Conformations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=5SE1350>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE1350>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE1350

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



