





NEOZED-FUSE LINK 400V GL/GG,GR.D02,
32A, COLLAPSIBLE BOX

Similar to image

Technical data:

Color coding of the fuse link		black
Current / for AC / rated value	A	32
Operating class of the fuse link		gG
Size of the fallback-system / acc. to DIN EN 60269-1		D02
Supply voltage • for AC / rated value	V	400
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	50
Design of the fuse link		NEOZED fuse links
mounting position		Any, preferably vertical
Protection class IP		IP20, with connected conductors
Climatic class		Up to 45°C at 95 % rel. humidity
Ambient temperature • minimum	°C	-5
• maximum	°C	40

Certificates/approvals:

General Product Approval		Test Certificates		other
		Special Test Certificate	Type Test Certificates/Test Report	Environmental Confirmations
GOST	VDE			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>


Industry Mall (Online ordering system)
<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<http://support.automation.siemens.com/WW/view/en/5SE2332/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2332

CAX-Online-Generator
<http://www.siemens.com/cax>

Tender specifications
[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)



last change:

Feb 12, 2014