

NEOZED-FUSE LINK 400V GL/GG,GR.D02, 40A, COLLAPSIBLE BOX



Figure similar

Model	
Product brand name	SETRON
Product designation	NEOZED fuse link
Design of the product	With silver-plated contact caps
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D02
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA
Dissipation	
Power loss [W]	

<ul style="list-style-type: none"> • for rated value of the current / at AC / in hot operating state / per pole 	3.1 W
<ul style="list-style-type: none"> • maximum 	3.1 W
Current / at AC / rated value	40 A

Main circuit	
Operating voltage / rated value	400 V
Operating current / rated value	40 A

Appearance	
Color coding of the fuse link	Black
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	13.4 g
Ambient temperature	
<ul style="list-style-type: none"> • minimum • maximum 	-5 °C 40 °C
Environmental category	Up to 45°C at 95 % rel. humidity

Certificates	
Equipment marking	
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2 	F F

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2340>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2340>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2340

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

