



MINIZED, Switch disconnector with Fuse, D02, 3-pole, In: 63 A, Un AC: 400 V

Model				
product brand name	MINIZED			
product designation	Switch disconnectors with fuses			
General technical data				
number of poles	3			
size of fuse system / acc. to DIN EN 60269-1	D02			
overvoltage category	4			
Voltage				
surge voltage resistance / rated value	6 kV			
Supply voltage				
operating voltage / at AC / rated value	400 V			
Protection class				
protection class IP	IP20, with connected conductors			
Dissipation				
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	7.5 W			
Current				
operational current / at AC / rated value	63 A			
Product details				
product feature / sealable	Yes			
Connections				
tightening torque / with screw-type terminals				
• minimum	2.5 N·m			
• maximum	3 N·m			
Mechanical Design				
height	70 mm			
width	81 mm			
depth	90 mm			
mounting position	any, preferably vertical			
net weight	455 g			
General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping	other



[Type Test Certificates/Test Report](#)



[Miscellaneous](#)

GL

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5SG7133>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG7133>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SG7133

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





