

5SM3647-4 RCCB TYPE B 80/4 300MA 4MW STD

Technical / CAx data

- Technical Data CAx data



Similar to image

RES.CURR. OP.CIRC. BR. SIQUENCE TYPE B SENS. TO. UNIV. CURRENT 80A 3+N-POL IFN 300MA 400V 4MW SHORT-TIME DELAYED

Technical data:		
Type, explanations		SIQUENCE RCCBs, type B Super resistant
Type of mounting		DIN-Rail
Mounting depth	mm	70
Design of the fault-current type		B
Number of poles		4
Resistance against short-circuit current	kA	10
Number of pitch units for width		4
Size of installation devices / acc. to DIN 43880		1
Release fault-current / rated value	mA	300
Switching function / short-term delayed		Yes
Product feature / selective type		No
Supply voltage frequency / rated value	Hz	60
Resistance against the impulse current / rated value	kA	3
Breaking capacity current / rated value	kA	0.8
Breaking capacity current / acc. to EN 60898 / rated value	kA	0.8
Supply voltage / for AC / rated value	V	400
Current / for AC / rated value	A	80
circuit-breaker / Design		5SM3
I ² t-value / permissible	A ² ·s	70,000
Let-through current / permissible	kA	7,500
rated current I _n / IEC, DIN/VDE / at 50 Cel	A	76.8
rated current I _n / IEC, DIN/VDE / at 70 Cel	A	64
rated current I _n / IEC, DIN/VDE / at 65 Cel	A	67.2
rated current I _n / IEC, DIN/VDE / at 45 Cel	A	80
Break time / max. / permissible	s	0.2
rated current I _n / IEC, DIN/VDE / at 40 Cel	A	80
rated current I _n / IEC, DIN/VDE / at 55 Cel	A	73.6

rated current In / IEC, DIN/VDE / at 60 Cel	A	70.4
Product extension / can be installed / supplementary device		Yes
Ambient conditions / degree of protection acc. to EN 60529		IP20
power loss	W	1.2
Short-circuit back-up fuse / maximum	A	100
Rated frequency fn / Hz		50 till 60Hz
CFC and silicone free		Yes
Rated currents In / A		25, 40, 63, 80
Terminal tightening torques		2,5 till 3,0 Nm
Terminal conductor cross-sections, solid and stranded		1,5 till 25 mm ²
Terminal conductor cross-sections, finely stranded with end sleeve		1.5 to 16mm ²
Climatic resistance acc. to IEC 60068-2-30		28 cycles (55 °C; 95 % rel. humidity)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Global Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/5SM3647-4/all>


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM3647-4

Tender specifications

Datanorm GAEB81 GAEB83 RTF TXT

 5SM3 RCCB, type A, 300 mA, 3P+N, 16A



last change:

May 20, 2011