

Connecting terminal, 50 mm<sup>2</sup> according to UL 489, 480Y/277V for LS 5SJ4...-HG Infeed busbar



Model	
product brand name	SENTRON
product designation	Connecting terminal
operating current / at AC / rated value	160 A
operating voltage / at AC / rated value	1 000 V

Connections	
tightening torque	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	<p>2 N·m</p> <p>3.5 N·m</p>

Mechanical Design	
height	51 mm
width	17.75 mm
length	31.2 mm
net weight	33 g

### Certificates



UR

[Miscellaneous](#)

EG-Konf.

**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3666-2HG>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/5ST3666-2HG>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3666-2HG](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3666-2HG)**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>