



Miniature circuit breaker 400 V 10kA, 3-pole, C, 8A, D=70 mm

| Model | |
|---|---------------------------------|
| product brand name | SENTRON |
| product designation | Miniature circuit breaker |
| General technical data | |
| number of poles | 3 |
| design of pole | 3P |
| tripping characteristic class | C |
| mechanical service life (operating cycles) typical | 10 000 |
| overvoltage category | III |
| degree of pollution | 3 |
| Voltage | |
| type of voltage of the operating voltage | AC |
| insulation voltage (U _i) | |
| • with single-phase operation at AC rated value | 440 V |
| • with multi-phase operation at AC rated value | 440 V |
| supply voltage with single-phase operation at AC rated value | 230 V |
| Supply voltage | |
| supply voltage | |
| • at AC rated value | 400 V |
| value range of the supply voltage frequency | 50/60 Hz |
| operating voltage at DC rated value maximum | 72 V |
| Protection class | |
| protection class IP | IP20, with connected conductors |
| Switching capacity | |
| switching capacity current | |
| • at DC according to IEC 60947-2 rated value | 15 kA |
| • according to EN 60898 rated value | 10 kA |
| • according to IEC 60947-2 rated value | 20 kA |
| energy limitation class | 3 |
| Dissipation | |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 0.9 W |
| Current | |
| operational current | |
| • at 35 °C rated value | 8 A |
| • at 40 °C rated value | 7.51 A |
| • at 45 °C rated value | 7.26 A |
| • at 50 °C rated value | 6.99 A |
| • at 55 °C rated value | 6.72 A |

| | |
|--|---|
| <ul style="list-style-type: none"> • at 60 °C rated value • at AC rated value | 6.43 A 8 A |
| suitability for operation | Mechanical engineering / industry |
| Product details | |
| product component | |
| <ul style="list-style-type: none"> • combined terminal top • combined terminal bottom • neutral conductor switching | Yes Yes No |
| product feature | |
| <ul style="list-style-type: none"> • properties for main switches in accordance with EN 60204-1 • halogen-free • sealable • silicon-free | Yes Yes Yes Yes |
| product extension installable supplementary devices | Yes |
| Short circuit | |
| short-circuit current breaking capacity (I _{cn}) | |
| <ul style="list-style-type: none"> • at AC according to UL 1077 and CSA C22.2 No.235 | 5 kA |
| Connections | |
| connectable conductor cross-section solid | |
| <ul style="list-style-type: none"> • minimum • maximum | 0.75 mm ² 35 mm ² |
| connectable conductor cross-section stranded | |
| <ul style="list-style-type: none"> • minimum • maximum | 0.75 mm ² 35 mm ² |
| connectable conductor cross-section finely stranded with core end processing | |
| <ul style="list-style-type: none"> • minimum • maximum | 0.75 mm ² 25 mm ² |
| AWG number as coded connectable conductor cross section | |
| <ul style="list-style-type: none"> • minimum • maximum | 18 4 |
| tightening torque [lbf-in] with screw-type terminals | |
| <ul style="list-style-type: none"> • minimum • maximum | 22 lbf-in 31 lbf-in |
| tightening torque with screw-type terminals | |
| <ul style="list-style-type: none"> • minimum • maximum | 2.5 N-m 3.5 N-m |
| position of power supply cord | Any |
| Mechanical Design | |
| height | 90 mm |
| width | 54 mm |
| depth | 76 mm |
| installation depth | 70 mm |
| number of modular width units | 3 |
| fastening method | Quick assembly system |
| mounting position | any |
| net weight | 457 g |
| Environmental conditions | |
| influence of the surrounding temperature standard | max. 95% to 55°C, max. 55% to 70°C, max. 35% to 75°C IEC / EN 60898-1, IEC / EN 60947-2 / UL1077 |
| vibration resistance according to IEC 60068-2-6 | ±1mm at 5 to 25Hz; 50m/s ² at 25 to 150Hz |
| ambient temperature during operation | |
| <ul style="list-style-type: none"> • minimum • maximum | -40 °C 70 °C |
| ambient temperature during storage | |
| <ul style="list-style-type: none"> • minimum • maximum | -40 °C 75 °C |
| number of test cycles for environmental testing according to IEC 60068-2-30 | 6 |
| General Product Approval | |



[Confirmation](#)



[Miscellaneous](#)

General Product Approval

EMC

Declaration of Conformity

[KC](#)



[Miscellaneous](#)



EG-Konf.



Test Certificates

Marine / Shipping

[Miscellaneous](#)

[Special Test Certificate](#)



LRS



RINA

Marine / Shipping

other

Railway



[Miscellaneous](#)

[Environmental Confirmations](#)

[Confirmation](#)

[Vibration and Shock](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SY4308-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SY4308-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY4308-7

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



CB

