



Article number

Text of invitation to tender

with integrated...-TH35-7.5002

### Technical Data

Rated operational voltage, AC		120 to 230
Output voltage, DC	V	29
Output current		640
Output current maximum	mA	640
Number of reactors Integrated		1
Number of installation bus lines		1
Type, explanations additionally		integrated reactor, 640 mA, additional output without reactor, 29 V DC
LED		Yes
Mounting type		modular installation device
Number of width units		4

### Certificates/approvals



UL

[Miscellaneous](#)

EIB/KNX

[Miscellaneous](#)

EG-Konf.

**Further information****Gamma-TD (Tech. Documentation, ETS Product database, Invitation to tender text)**<http://www.siemens.com/gamma-td?ssn=5WG1125-1AB22>**Gamma - Catalogue**<http://www.siemens.com/gamma-catalogue>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=5WG1125-1AB22&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=5WG1125-1AB22&lang=en)**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5WG1125-1AB22>

last modified:

02/08/2019