

SIPLUS ET200S IM151-3 ST -25 ... +60 DGR C BASED ON
6ES7151-3AA23-0AB0

Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Extended ambient conditions	
Relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
With condensation/maximum/tested in accordance with IEC 60068-2-38	100 %
Resistance	
to biologically active substances / conformity with EN 60721-3-3	Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
to chemically active substances / conformity with EN 60721-3-3	Yes
to mechanically active substances / conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Min.	-25 °C ; = Tmin
max.	60 °C ; = Tmax
Dimensions	
Width	60 mm
Height	119.5 mm
Depth	75 mm
Status	Aug 8, 2013