

SIPLUS ET200S TM-E15S26-A1 -40 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6ES7193-4CA40-0AA0 5 PIECES PER PACKAGING UNIT . FOR ELECTRONIC MODULES WIDTH 15MM, SCREW-TYPE TERMINALS 2X6 TERMINAL CONNECTIONS WITH TERMINAL LEAD TO AUX1, AUX1 IN LINE

General information	
Delivery quantity in pieces	5
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Extended ambient conditions	
Relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
with condensation / maximum	100 % ; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance	
to biologically active substances / conformity with EN 60721-3-3	Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
to chemically active substances / conformity with EN 60721-3-3	Yes ; Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
to mechanically active substances / conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Min.	-40 °C ; = Tmin
max.	70 °C ; = Tmax
Dimensions	
Width	15 mm
Height	157 mm
Depth	43 mm
Weight	

---

**Weight, approx.**

83 g

Status

Jul 1, 2013