

### Product type designation

### SIPLUS NET CP 342-5

SIPLUS NET CP 342-5 PROFIBUS -25...+70°C based on 6GK7342-5DA03-0XE0 . Communications processor CP 342-5 for connecting SIMATIC S7-300 to PROFIBUS, DP, S5-compatible, PG/OP and S7 communication



Figure similar

### Transmission rate

#### Transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

### Interfaces

#### Number of interfaces / acc. to Industrial Ethernet

0

#### Number of electrical connections

- at the 1st interface / acc. to PROFIBUS 1
- for power supply 1

#### Type of electrical connection

- at the 1st interface / acc. to PROFIBUS 9-pin Sub-D socket (RS485)
- for power supply 4-pole terminal block

### Supply voltage, current consumption, power loss

#### Type of voltage / of the supply voltage

DC

#### Supply voltage / 1 / from backplane bus

5 V

#### Supply voltage / external

24 V

#### Relative positive tolerance / at DC / at 24 V

20 %

Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	0.15 A
• from external supply voltage / at DC / at 24 V / typical	0.25 A
Power loss [W]	6.75 W
Ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• in horizontal mounting position / during operation	70 ... -25 °C
• during storage and transport	70 ... -40 °C
Installation altitude / at height above sea level / maximum	5000 m
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	100 %
• with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
• with condensation / acc. to IEC 60068-2-38 / maximum	100 %
Resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Coating / for equipped printed circuit board / acc. to EN 61086	Yes
Type of test / of the coating / acc. to MIL-I-46058C	Yes
Product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes
Protection class IP	IP20

#### Design, dimensions and weight

Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm

Net weight	0.3 kg
------------	--------

### Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> <li>• per CPU / maximum</li> </ul>	4

### Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
---	----

Amount of data	
<ul style="list-style-type: none"> <li>• as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	240 byte

### Performance data / PROFIBUS DP

Service / as DP master	
<ul style="list-style-type: none"> <li>• DPV0</li> </ul>	Yes

Number of DP slaves / on DP master / usable	124
---	-----

Amount of data	
<ul style="list-style-type: none"> <li>• of the address area of the inputs / as DP master / total</li> </ul>	2160 byte
<ul style="list-style-type: none"> <li>• of the address area of the outputs / as DP master / total</li> </ul>	2160 byte
<ul style="list-style-type: none"> <li>• of the address area of the inputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• of the address area of the outputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• of the address area of the diagnostic data / per DP slave</li> </ul>	240 byte

Service / as DP slave	
<ul style="list-style-type: none"> <li>• DPV0</li> </ul>	Yes

Amount of data	
<ul style="list-style-type: none"> <li>• of the address area of the inputs / as DP slave / total</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>• of the address area of the outputs / as DP slave / total</li> </ul>	240 byte

### Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	16

### Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> <li>• without DP / maximum</li> </ul>	32
<ul style="list-style-type: none"> <li>• with DP / maximum</li> </ul>	28

## Performance data / telecontrol

### Protocol / is supported

- TCP/IP

No

## Product functions / management, configuration

### Configuration software

- required

STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher

## Further Information / Internet Links

### Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<http://support.automation.siemens.com>

## Security information

### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

06/06/2019