

SIPLUS S7-400 BGT UR1 18SLOT AL -25 ... +70 DEGREES C
 WITH CONFORMAL COATING BASED ON 6ES7400-1TA11-0AA0 .
 CENTRALIZED AND DISTRIBUTED WITH 18 SLOTS, 2
 REDUNDANT PS PLUGGABLE



Figure similar

Hardware configuration	
Rack	
• Communication bus	Yes
• P bus	Yes
Slots	
• Number of single-width slots, max.	18
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Extended ambient conditions	

- relative to ambient temperature-atmospheric pressure-installation altitude

Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max.

100 %; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)

Resistance

- against biologically active substances / conformity with EN 60721-3-3
- against chemically active substances / conformity with EN 60721-3-3
- against mechanically active substances / conformity with EN 60721-3-3

Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation in corrosive atmospheres!

Yes; Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation in corrosive atmospheres!

Dimensions

Width	482.5 mm
Height	290 mm
Depth	27.5 mm

Weights

Weight, approx.	3 kg
-----------------	------

last modified: 03/11/2017