

SIPLUS S7-400 UR2-H RACK -25 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6ES7400-2JA10-0AA0 . CENTRALIZED AND DISTRIBUTED WITH 2 X 9 SLOTS




Figure similar

Hardware configuration	
Rack	
• Communication bus	Yes
• P bus	Yes
Slots	
• Number of single-width slots, max.	18
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Extended ambient conditions	

- relative to ambient temperature-atmospheric pressure-installation altitude

Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max.

100 %; RH incl. condensation/frost (no commissioning under condensation conditions)

Resistance

- against biologically active substances / conformity with EN 60721-3-3
- against chemically active substances / conformity with EN 60721-3-3
- against mechanically active substances / conformity with EN 60721-3-3

Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Dimensions

Width	482.5 mm
Height	290 mm
Depth	27.5 mm

Weights

Weight, approx.	3 000 g
-----------------	---------

last modified: 03/11/2017