

Product type designation

SIPLUS NET CP 443-1

SIPLUS NET CP443-1 FOR MEDIAL STRESS WITH CONFORMAL COATING BASED ON 6GK7443-1EX30-0XE0 . 2 X 10/100 MBIT/S (IE SWITCH); RJ 45 PORTS; ISO; TCP; UDP; PROFINET-IO CONTROLLER; S7-COMMUNICATION; OPEN COMMUNICATION (SEND/RE-CEIVE); S7-ROUTING; IP-CONFIGURATION VIA DHCP/BLOCK; IP ACCESS CONTROL LIST; TIME-SYNCHRONISATION; EXTENDED WEB-DIAGNOSIS; FAST STARTUP; PROFIENERGY SUPPORT



Figure similar

Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

2

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet

2

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

design of the removable storage / C-PLUG

No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Relative symmetrical tolerance / at DC

- at 5 V

5 %

Consumed current

<ul style="list-style-type: none"> • from backplane bus / at DC / at 5 V / typical 	1.4 A
Power loss [W]	8.6 W
Permitted ambient conditions	
Ambient temperature <ul style="list-style-type: none"> • during operation • during storage • during transport 	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Ambient condition / relating to ambient temperature - air pressure - installation altitude	-25 ... +70°C at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // -25 ... +60°C at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // -25 ... +50°C at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity / with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
Resistance to biologically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 	Yes; Compliance with EN 60721-3-3, Class 3B2 mold, fungus, and sponge spores (except fauna). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to chemically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to mechanically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation!
Protection class IP	IP20
Design, dimensions and weight	
Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.7 kg
Product properties, functions, components / general	
Number of units <ul style="list-style-type: none"> • per CPU / maximum • Note 	14 max. 4 as PN IO ctrl.
Performance data / open communication	
Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
Amount of data <ul style="list-style-type: none"> • as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte

<ul style="list-style-type: none"> • as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
Number of possible connections / for open communication	
<ul style="list-style-type: none"> • by means of T blocks / maximum 	64
Amount of data	
<ul style="list-style-type: none"> • as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum 	1452 byte

Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	128
<ul style="list-style-type: none"> • with PG connections / maximum 	2
<ul style="list-style-type: none"> • Note 	when using several CPUs

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	128
---	-----

Performance data / PROFINET communication / as PN IO-Controller

Product function / PROFINET IO controller	Yes
Number of PN IO devices / on PROFINET IO controller / usable / total	128
Number of PN IO IRT devices / on PROFINET IO controller / usable	64
Number of external PN IO lines / with PROFINET / per rack	4
Amount of data	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	4 Kibyte
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	4 Kibyte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte

- as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum
- as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum

240 byte

240 byte

Performance data / telecontrol

Protocol / is supported	
<ul style="list-style-type: none"> • TCP/IP 	Yes
Product function / MIB support	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 • DCP • LLDP 	Yes Yes Yes
Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.5 SP3 or higher / STEP 7 Professional V12 (TIA Portal) or higher

Product functions / Diagnosis

Product function / Web-based diagnostics	Yes
--	-----

Product functions / switch

Product feature / Switch	Yes
Product function	
<ul style="list-style-type: none"> • switch-managed • with IRT / PROFINET IO switch • Configuration with STEP 7 	No Yes Yes

Product functions / Redundancy

Product function	
<ul style="list-style-type: none"> • Ring redundancy • Redundancy manager 	Yes Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

03/09/2017