

CHARGING STATION FOR MOBILE PANEL 277(F) IWLAN WITH
 LOCK FOR CHARGE AND HOLD THE MOBILE PANEL 277(F)
 IWLAN CHARGING OF 2 SPARE BATTERIES



Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	3.2 A
Power	
Active power input, typ.	77 W
Degree and class of protection	
Degree of protection acc. to EN 60529	IP65
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	

Ambient temperature during operation

- Operation (vertical installation) 0 to +40 °C
 - For vertical installation, min. 0 °C
 - For vertical installation, max. 40 °C

Ambient temperature during storage/transportation

- min. -20 °C
- max. 60 °C

Relative humidity

- Operation, max. 85 %

Dimensions

Width	208 mm
Height	333 mm
Depth	75 mm

Weights

Weight (without packaging)	1.1 kg
----------------------------	--------

Other

Usable in the following products

- Product 1 [6AV6645-0EB01-0AX1](#)
- Product 2 [6AV6645-0EC01-0AX1](#)
- Product 3 [6AV6645-0EF01-0AX1](#)
- Product 4 [6AV6645-0GB01-0AX1](#)
- Product 5 [6AV6645-0GC01-0AX1](#)
- Product 6 [6AV6645-0GF01-0AX1](#)
- Product 7 [6AV6645-0DD01-0AX1](#)
- Product 8 [6AV6645-0DE01-0AX1](#)
- Product 9 [6AV6645-0FD01-0AX1](#)
- Product 10 [6AV6645-0FE01-0AX1](#)
- Product 11 [6AV6645-0DB01-0AX0](#)
- Product 12 [6AV6645-0DC01-0AX0](#)
- Product 13 [6AV6645-0DD01-0AX0](#)
- Product 14 [6AV6645-0DE01-0AX0](#)

last modified: 07/31/2017