

SIMATIC IFP2200 V2, 22" multi-touch display (16:9) with 1920x1080 pixel resolution, built-in unit, for 24 V DC, display port/DVI interface, including DP/USB cable 1.8 m, on the rear USB, neutral design



Figure similar

General information	
Product type designation	IFP2200
Short designation	SIMATIC IFP2200 V2
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in; 22"
Screen diagonal [cm]	56 cm
Display width	476 mm
Display height	268 mm
Number of colors	16 777 216; 24 bit
Viewing angle	170° x 170°
Resolution (pixels)	
• Image resolution	1 920 x 1 080
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
• Pixel size, horizontal	0.2475 mm
• Pixel size, vertical	0.2475 mm
General features	
• Brightness/contrast	250 cd/m <sup>2</sup> / 1 000:1
• Detachable from computer unit	5 m
• Luminance	250 cd/m <sup>2</sup>
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	multi-touch screen
Keyboard fonts	
• Function keys	No
— Number of function keys	0
Touch operation	
• Design as touch screen	Yes; Projective-capacitive
• Design as multi-touch screen	Yes; Projective-capacitive
• Monitor keyboard	Yes; If supported by operating system
Installation type/mounting	
Design	Built-in unit

Front mounting	Yes
VESA mounting	Yes; VESA 100 x 100 integrated
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°
<b>Supply voltage</b>	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
<b>Input current</b>	
Current consumption (rated value)	1 A
Current consumption, max.	1.3 A
Inrush current, max.	2 A
Starting current inrush I <sup>2</sup> t	0.5 A <sup>2</sup> ·s
<b>Power loss</b>	
Power loss, typ.	24 W
Power loss, max.	30 W
<b>Interfaces</b>	
Number of USB interfaces	2; USB 2.0 type A
USB on the rear	Yes; 2x onboard
<b>Video interfaces</b>	
<ul style="list-style-type: none"> <li>analog video signal (VGA)</li> </ul>	No
<ul style="list-style-type: none"> <li>DVI-D</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DisplayPort</li> </ul>	Yes; Display port V1.2
<b>Touch interfaces</b>	
<ul style="list-style-type: none"> <li>USB</li> </ul>	Yes
<b>Degree and class of protection</b>	
IP (at the front)	IP65
NEMA (front)	
<ul style="list-style-type: none"> <li>Enclosure Type 4 at the front</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Enclosure Type 4x at the front</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Enclosure Type 12 at the front</li> </ul>	Yes
<b>Standards, approvals, certificates</b>	
Certificate of suitability	hazardous zone 2/22; shipbuilding
CE mark	Yes
UL approval	Yes; cULus, cUL
FM approval	Yes; Class I Div. 2
EAC (formerly Gost-R)	Yes
EMC	CE, EN 55011, EN 61000-6-4, EN 61000-6-2
<b>Use in hazardous areas</b>	
<ul style="list-style-type: none"> <li>ATEX Zone 2</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>ATEX Zone 22</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>IECEX Zone 2</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>IECEX Zone 22</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>FM Class I Division 2</li> </ul>	Yes; Available soon
<b>Marine approval</b>	
<ul style="list-style-type: none"> <li>Germanischer Lloyd (GL)</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>American Bureau of Shipping (ABS)</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>Bureau Veritas (BV)</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>Det Norske Veritas (DNV)</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes; Available soon
<ul style="list-style-type: none"> <li>Nippon Kaiji Kyokai (Class NK)</li> </ul>	Yes; Available soon
<b>Ambient conditions</b>	
Ambient temperature during operation	

• min.	0 °C
• max.	45 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C
• max.	60 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	3 500 m
<b>Relative humidity</b>	
• Operation, max.	90 %; no condensation
<b>Vibrations</b>	
• Vibration load in operation	10 m/s <sup>2</sup>
• Vibration load during transport/storage	10 m/s <sup>2</sup>
<b>Shock testing</b>	
• Shock load during operation	150 m/s <sup>2</sup>
• shock acceleration during storage/transport	250 m/s <sup>2</sup>
<b>Mechanics/material</b>	
Enclosure material (front)	With neutral design
• Aluminum	Yes
• Aluminum casting	Yes
• Glass	Yes; at front
Enclosure material (rear)	aluminum
<b>Dimensions</b>	
Width of the housing front	529 mm
Height of housing front	331 mm
Mounting cutout, width	382 mm; Tolerance: +1 mm
Mounting cutout, height	241 mm; Tolerance: +1 mm
Overall depth	63.4 mm
<b>Weights</b>	
Weight without packaging	6.4 kg
Weight incl. packaging	8.4 kg
<b>last modified:</b>	1/16/2021 