

LOGO! TD TEXTDISPLAY, 6 LINES, 3 BACKGROUND COLORS 2  
ETHERNET PORTS ACCESSORIES, FOR LOGO! 8



## General information

Suitability for use Can be used with LOGO! 8 and higher

## Display

Design of display FSTN

### Line display

- Number of lines 6
- Number of characters per line 20

### Backlighting

- Type of backlighting LED

## Control elements

### Keyboard fonts

- System keys Yes
  - Number of configurable system keys 0
- alphanumeric keyboard No

## Installation type/mounting

Wall mounting/direct mounting No

## Supply voltage

Type of supply voltage	AC/DC
Rated value (DC)	12 V; 12 V DC, 12/24 V AC/DC
<b>Power loss</b>	
Power loss, typ.	1.8 W
<b>Digital inputs</b>	
Number of digital inputs	0
<b>Interfaces</b>	
Number of RS 485 interfaces	0
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	No
<b>Degree and class of protection</b>	
IP (at the front)	IP65
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes
FM approval	Yes
KC approval	Yes
Marine approval	
• American Bureau of Shipping (ABS)	Yes
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
<b>Accessories</b>	
belongs to product	LOGO!
<b>Mechanics/material</b>	
Design of housing	plastic
<b>Dimensions</b>	
Width	128.2 mm
Height	86 mm
Depth	38.7 mm
Overall depth	38.7 mm
<b>Weights</b>	
Weight, approx.	220 g
<b>Scope of supply</b>	
Delivery quantity in pieces	1
<b>last modified:</b>	08/29/2017