

SITOP PSU100S 20 A STABILIZED POWER SUPPLY INPUT:
120/230 V AC OUTPUT: 24 V/20 A DC



Technical specifications

Product	SITOP PSU100S
Power supply, type	24 V/20 A

Input

Input	1-phase AC
Supply voltage 1 with AC Rated value	120 V
Supply voltage 2 with AC Rated value	230 V
• Note	Automatic range selection
Input voltage 1 with AC	85 ... 132 V
Input voltage 2 with AC	176 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at lout rated, min.	20 ms
Mains buffering	at $V_{in} = 120/230$ V
Rated line frequency	50 ... 60 Hz
Rated line range	47 ... 63 Hz
Input current at rated input voltage 120 V Rated value	7.5 A
Input current at rated input voltage 230 V Rated value	3.5 A

Switch-on current limiting (+25 °C), max.	11 A
I^2t , max.	10 A ² ·s
Built-in incoming fuse	T 10 A (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C or circuit-breaker 3RV2411-1JA10 (120 V) or 3RV2411-1FA10 (230 V)

Output

Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	24 V
Total tolerance, static \pm	3 %
Static mains compensation, approx.	0.5 %
Static load balancing, approx.	1 %
Residual ripple peak-peak, max.	150 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Adjustment range	24 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 480 W
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 50 V DC/ 0.3 A) for "24 V OK"
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	50 ms
Voltage increase time of the output voltage maximum	500 ms
Rated current value I_{out} rated	20 A
Current range	0 ... 20 A
<ul style="list-style-type: none"> Note 	24 A up to +45°C; +60 ... +70 °C: Derating 5%/K
Active power supplied typical	480 W
Short-term overload current on short-circuiting during the start-up typical	35 A
Duration of overloading capability for excess current on short-circuiting during the start-up	100 ms
Short-term overload current at short-circuit during operation typical	35 A
Duration of overloading capability for excess current at short-circuit during operation	100 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at V_{out} rated, I_{out} rated, approx.	90 %
Power loss at V_{out} rated, I_{out} rated, approx.	53 W

Closed-loop control

Dynamic mains compensation (V_{in} rated ± 15 %), max.	1 %
---	-----

Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ.	3 %
Setting time maximum	10 ms

Protection and monitoring

Output overvoltage protection	Yes, according to EN 60950-1
Current limitation, typ.	21 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current RMS value maximum	7 A
Enduring short circuit current RMS value typical	overload capability 150 % I _{out} rated up to 5 s/min
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current maximum	3.5 mA
Leakage current typical	1 mA
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; in preparation: cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
Certificate of suitability IECEx	No
Certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
Marine approval	GL
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature during operation	0 ... 70 °C
• Note	with natural convection
Ambient temperature during transport	-40 ... +85 °C
Ambient temperature during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	screw-type terminals
Connections Supply input	L1, N, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded

Connections Output	+, -: 2 screw terminals each for 0.2 ... 4 mm ²
Connections Auxiliary	13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ²
Width of the enclosure	115 mm
Height of the enclosure	145 mm
Depth of the enclosure	150 mm
Installation width	120 mm
Installation height	245 mm
Weight, approx.	2.4 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Mounting type wall mounting	No
Mounting type Standard rail mounting	Yes
Mounting type S7 rail mounting	No
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Buffer module
Mechanical accessories	Device identification label 20 mm × 7 mm, pastel-turquoise 3RT1900-1SB20
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)