

SITOP PSU8200 24 V/20 A
 SITOP PSU8200 20A STABILIZED POWER SUPPLY INPUT: 120-230 V AC 110-220 V DC OUTPUT: 24 V/20 A DC



| Input | |
|--|--|
| Input | 1-phase AC or DC |
| Supply voltage | |
| <ul style="list-style-type: none"> at DC | 110 ... 220 V |
| Rated voltage value V_{in} rated | 120 ... 230 V |
| Voltage range AC | 85 ... 275 V |
| <ul style="list-style-type: none"> Note | Derating of temperature necessary down to 50 °C at $V_{in} < 100$ V AC or DC |
| Input voltage | |
| <ul style="list-style-type: none"> at DC | 88 ... 350 V |
| Wide-range input | Yes |
| Mains buffering at I_{out} rated, min. | 20 ms; at $V_{in} = 230$ V |
| Rated line frequency | 50 ... 60 Hz |
| Rated line range | 45 ... 65 Hz |
| Input current | |
| <ul style="list-style-type: none"> at rated input voltage 120 V at rated input voltage 230 V | 4.6 A 2.5 A |
| Switch-on current limiting (+25 °C), max. | 20 A |
| I^2t , max. | 5 A ² ·s |

| | |
|---|--|
| Built-in incoming fuse | Yes |
| Protection in the mains power input (IEC 898) | Recommended miniature circuit breaker at 1-phase operation: 10 A characteristic C; required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2711-1HD10 (UL 489) at 120 V or 3RV2711-1ED10 (UL 489) at 230 V |

Output

| | |
|---|---|
| Output | Controlled, isolated DC voltage |
| Rated voltage V_{out} DC | 24 V |
| Total tolerance, static \pm | 3 % |
| Static mains compensation, approx. | 0.1 % |
| Static load balancing, approx. | 0.3 % |
| Residual ripple peak-peak, max. | 100 mV |
| Residual ripple peak-peak, typ. | 80 mV |
| Spikes peak-peak, max. (bandwidth: 20 MHz) | 200 mV |
| Spikes peak-peak, typ. (bandwidth: 20 MHz) | 100 mV |
| Adjustment range | 24 ... 28.8 V |
| Product function Output voltage adjustable | Yes |
| Output voltage setting | via potentiometer |
| Status display | Green LED for 24 V OK |
| Signaling | Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK" |
| On/off behavior | No overshoot of V_{out} (soft start) |
| Startup delay, max. | 0.25 s |
| Voltage rise, typ. | 50 ms |
| Rated current value I_{out} rated | 20 A |
| Current range | 0 ... 20 A |
| • Note | +60 ... +70 °C: Derating 3%/K |
| Active power supplied typical | 480 W |
| Short-term overload current | |
| • at short-circuit during operation typical | 60 A |
| Duration of overloading capability for excess current | |
| • at short-circuit during operation | 25 ms |
| Constant overload current | |
| • on short-circuiting during the start-up typical | 30 A |
| Parallel switching for enhanced performance | Yes; switchable characteristic |
| Numbers of parallel switchable units for enhanced performance | 2 |

Efficiency

| | |
|---|------|
| Efficiency at V_{out} rated, I_{out} rated, approx. | 93 % |
| Power loss at V_{out} rated, I_{out} rated, approx. | 42 W |

Closed-loop control

| | |
|---|-------|
| Dynamic mains compensation (V_{in} rated ± 15 %), max. | 0.5 % |
|---|-------|

| | |
|--|------|
| Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ. | 1 % |
| Load step setting time 50 to 100%, typ. | 1 ms |
| Load step setting time 100 to 50%, typ. | 1 ms |
| Setting time maximum | 5 ms |

Protection and monitoring

| | |
|--|--|
| Output overvoltage protection | < 33 V |
| Current limitation, typ. | 21.5 A |
| Property of the output Short-circuit proof | Yes |
| Short-circuit protection | Alternatively, constant current characteristic approx. 23 A or latching shutdown |
| Enduring short circuit current RMS value <ul style="list-style-type: none"> • typical | 23 A |
| Overcurrent overload capability in normal operation | overload capability 150 % I _{out} rated up to 5 s/min |
| Overload/short-circuit indicator | LED yellow for "overload", LED red for "latching shutdown" |

Safety

| | |
|--|---|
| Primary/secondary isolation | Yes |
| Galvanic isolation | Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178 |
| Protection class | Class I |
| Leakage current <ul style="list-style-type: none"> • maximum • typical | 3.5 mA 1 mA |
| CE mark | Yes |
| UL/CSA approval | Yes |
| UL/cUL (CSA) approval | cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 |
| Explosion protection | IECEX Ex nA nC IIC T3 Gc; ATEX (EX) II 3G Ex nA nC IIC T3 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T3 |
| Certificate of suitability IECEx | Yes |
| Certificate of suitability NEC Class 2 | No |
| FM approval | - |
| CB approval | No |
| Marine approval | GL, ABS |
| Degree of protection (EN 60529) | IP20 |

EMC

| | |
|-----------------------------|------------------|
| Emitted interference | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2 |
| Noise immunity | EN 61000-6-2 |

Operating data

| | |
|--|----------------|
| Ambient temperature <ul style="list-style-type: none"> • during operation | -25 ... +70 °C |
|--|----------------|

| | |
|--|---|
| <ul style="list-style-type: none"> — Note • during transport • during storage | with natural convection -40 ... +85 °C -40 ... +85 °C |
| Humidity class according to EN 60721 | Climate class 3K3, no condensation |

| Mechanics | |
|--|---|
| Connection technology | screw-type terminals |
| Connections | |
| <ul style="list-style-type: none"> • Supply input | L, N, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded |
| <ul style="list-style-type: none"> • Output | +, -: 2 screw terminals each for 0.2 ... 4 mm ² |
| <ul style="list-style-type: none"> • Auxiliary | 13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ² |
| Width of the enclosure | 90 mm |
| Height of the enclosure | 125 mm |
| Depth of the enclosure | 125 mm |
| Weight, approx. | 1.2 kg |
| Product feature of the enclosure housing for side-by-side mounting | Yes |
| Installation | Snaps onto DIN rail EN 60715 35x7.5/15 |
| Electrical accessories | Buffer module |
| Mechanical accessories | Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20 |
| MTBF at 40 °C | 667 048 h |
| Other information | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |