

# SIEMENS

## Product data sheet

**6ES7134-4GB01-0AB0**


SIMATIC DP,  
ELECTRONIC MODULE FOR ET 200S,  
2 AI STAND. I-2DMU 15 MM WIDE,  
4 .. 20mA;  
13 BIT FOR 2-WIRE TRANSDUCER CYCLE TIME 65  
MS/CHANNEL WITH LED SF (GROUP FAULT)

Supply voltage	
Load voltage L+	
Rated value (DC)	24 V ; From power module
Reverse polarity protection	Yes ; Destruction limit 35 mA per channel
Input current	
from load voltage L+ (without load), max.	80 mA
from backplane bus 3.3 V DC, max.	10 mA
Power losses	
Power loss, typ.	0.6 W
Address area	
Address space per module	
Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
Cable length, shielded, max.	200 m

Cycle time (all channels) max.	Number of active channels per module x basic conversion time
permissible input current for current input (destruction limit), max.	40 mA
<b>Input ranges</b>	
Voltage	No
Current	Yes
Thermocouple	No
Resistance thermometer	No
Resistance	No
<b>Input ranges (rated values), currents</b>	
4 to 20 mA	Yes ; on 50 ohms
<b>Analog value creation</b>	
Measurement principle	integrating
<b>Integrations and conversion time/ resolution per channel</b>	
Resolution with overrange (bit including sign), max.	13 bit ; 4 to 20 mA: 13 bits
Integration time, ms	16.7 / 20 ms
Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz
Conversion time (per channel)	65 ms ; 55 / 65 ms
<b>Smoothing of measured values</b>	
parameterizable	Yes ; In four stages by means of digital filtering
Step: None	Yes ; 1 x cycle time
Step: Low	Yes ; 4 x cycle time
Step: Medium	Yes ; 32 x cycle time
Step: High	Yes ; 64 x cycle time
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
Burden of 2-wire transmitter, max.	750 $\Omega$
<b>Errors/accuracies</b>	
Linearity error (relative to input area)	+/- 0,01 %
Temperature error (relative to input area)	+/- 0,005 %/K
Crosstalk between the inputs, min.	-50 dB

Repeat accuracy in settled status at 25 °C (relative to input area)	+/- 0,05 %
<b>Operational limit in overall temperature range</b>	
Current, relative to input area	+/- 0,6 %
<b>Basic error limit (operational limit at 25 °C)</b>	
Current, relative to input area	+/- 0,4 %
<b>Interference voltage suppression for <math>f = n \times (f_l \pm 1\%)</math>, <math>f_l</math> = interference frequency</b>	
Series mode interference (peak value of interference < rated value of input range), min.	70 dB
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnoses</b>	
Wire break	Yes
Group error	Yes
Overflow/underflow	Yes
<b>Diagnostics indication LED</b>	
Group error SF (red)	Yes
<b>Isochronous mode</b>	
Isochronous mode	No
<b>Parameter</b>	
Remark	4 bytes
Measurement type/range	deactivated / 4 to 20 mA
Group diagnostics	Disable / enable
Overflow/underflow	Disable/enable
<b>Galvanic isolation</b>	
<b>Galvanic isolation analog inputs</b>	
between the channels	No
between the channels and the backplane bus	Yes
between the channels and the load voltage L+	No
<b>Isolation</b>	
Isolation checked with	500 VDC
<b>Dimensions and weight</b>	
<b>Dimensions</b>	
Width	15 mm
Height	81 mm

---

Depth	52 mm
Weight	
Weight, approx.	40 g
Status	May 16, 2011