

SIMATIC DP, Electronics module 2 AI I High Feature for ET 200S, 15 mm width, Cycle time per module: 0.5 ms, +/-20mA; 15 bit+sign, 4..20mA; 15 bit, Operational limit +/-0.1% with SF LED (group fault)



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	48 mA
from backplane bus 3.3 V DC, max.	10 mA
Output voltage	
Power supply to the transmitters	
• present	Yes
• short-circuit proof	Yes
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	

Number of analog inputs	2
permissible input current for current input (destruction limit), max.	50 mA
Cycle time (all channels) max.	0.5 ms; 0.5 ms for 2 channels without noise suppression, 18 / 21 ms per channel with noise suppression
Input ranges	
• Voltage	No
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz / no
• Conversion time (per channel)	0.04 ms; Without noise suppression 17/20 ms per channel with error
Smoothing of measured values	
• parameterizable	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time
• Step: None	Yes; 1x
• Step: low	Yes; 4x
• Step: Medium	Yes; 16x
• Step: High	Yes; 32x
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max.	750 Ω
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.03 %
Temperature error (relative to input range), (+/-)	0.003 %/K
Crosstalk between the inputs, min.	-100 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.01 %
Operational error limit in overall temperature range	

<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.1 %; 0.2% without interference frequency suppression
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.05 %; 0.1% without interference frequency suppression
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
<ul style="list-style-type: none"> • Series mode interference (peak value of interference < rated value of input range), min. 	90 dB
<ul style="list-style-type: none"> • Common mode interference (USS < 2.5 V), min. 	100 dB

Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes

Interrupts/diagnostics/status information	
Alarms	
<ul style="list-style-type: none"> • Hardware interrupt 	Yes
Diagnostic messages	
<ul style="list-style-type: none"> • Wire-break 	Yes; Measuring range 4 to 20 mA only
<ul style="list-style-type: none"> • Group error 	Yes
<ul style="list-style-type: none"> • Overflow/underflow 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	Yes

Parameter	
Remark	12 bytes, 4 bytes in compatibility mode
Diagnostics wire break	Disable / enable
Measurement type/range	deactivated / ± 20 mA / 4 to 20 mA
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable

Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> • between the channels 	No; however, increased permissible potential difference between the inputs.
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> • Between the channels and load voltage L+ 	Yes

Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm

Weights	
Weight, approx.	45 g

last modified: 10/05/2018