

- MSI

No

CiR – Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	No

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, max.	45 mA; without sensor supply
---------------------------	------------------------------

Encoder supply

24 V encoder supply	
• 24 V	Yes
• Short-circuit protection	Yes
• Output current, max.	50 mA; Total current for both channels (two-wire)
Additional 24 V encoder supply	
• 24 V	Yes
• Short-circuit protection	Yes; Module-wise
• Output current, max.	200 mA; Total current for both channels (four-wire)

Power loss

Power loss, typ.	1.1 W
------------------	-------

Address area

Address space per module	
• Address space per module, max.	4 byte; + 1 byte for QI information

Hardware configuration

Selection of BaseUnit for connection variants	
• 1-wire connection	BU type A0, A1
• 2-wire connection	BU type A0, A1
• 4-wire connection	BU type A0, A1

Analog inputs

Number of analog inputs	2
• For current measurement	2
permissible input current for current input (destruction limit), max.	50 mA
Cycle time (all channels), min.	500 μ s
Input ranges (rated values), currents	
• 0 to 20 mA	Yes; 15 bit
• Input resistance (0 to 20 mA)	130 Ω ; 90 ohms with two wires

<ul style="list-style-type: none"> • -20 mA to +20 mA • Input resistance (-20 mA to +20 mA) • 4 mA to 20 mA • Input resistance (4 mA to 20 mA) 	Yes; 16 bit incl. sign 130 Ω Yes; 15 bit 130 Ω; 90 ohms with two wires
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m

Analog value generation for the inputs

Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Interference voltage suppression for interference frequency f1 in Hz • Conversion time (per channel) 	16 bit Yes 16.6 / 50 / 60 Hz / off 50 ms @ 60 Hz, 60 ms @ 50 Hz, 180 ms @ 16.6 Hz, 500 μs without filter
Smoothing of measured values	
<ul style="list-style-type: none"> • Number of smoothing levels • parameterizable • Step: None • Step: low • Step: Medium • Step: High 	4 Yes Yes; 1x conversion time Yes; 4x conversion time Yes; 8x conversion time Yes; 16x conversion time

Encoder

Connection of signal encoders	
<ul style="list-style-type: none"> • for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max. • for current measurement as 4-wire transducer 	Yes 650 Ω Yes

Errors/accuracies

Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.5 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.3 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
<ul style="list-style-type: none"> • Series mode interference (peak value of interference < rated value of input range), min. • Common mode voltage, max. 	70 dB 10 V

- Common mode interference, min. 90 dB

Isochronous mode

- Isochronous operation (application synchronized up to terminal) No

Interrupts/diagnostics/status information

- Diagnostics function Yes

Alarms

- Diagnostic alarm Yes
- Limit value alarm No

Diagnostic messages

- Monitoring the supply voltage Yes
- Wire-break Yes; at 4 to 20 mA
- Short-circuit Yes; Short-circuit of the encoder supply
- Group error Yes
- Overflow/underflow Yes

Diagnostics indication LED

- Monitoring of the supply voltage (PWR-LED) Yes; Green PWR LED
- Channel status display Yes; Green LED
- for channel diagnostics No
- for module diagnostics Yes; green/red DIAG LED

Potential separation

Potential separation channels

- between the channels No
- between the channels and backplane bus Yes
- between the channels and the power supply of the electronics Yes

Permissible potential difference

- between the inputs (UCM) 10 Vpp

Isolation

- Isolation tested with 707 V DC (type test)

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. -30 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -30 °C
- vertical installation, max. 50 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m

Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

Weights

Weight, approx.	32 g
-----------------	------

last modified: 08/03/2019