



SIMATIC ET 200SP, ANALOG OUTPUT MODULE, AQ 4XU/I STANDARD, FITS TO BU-TYPE A0, A1, COLOR CODE CC00, MODULE DIAGNOSIS, 16BIT, +/-0,3%

Product type designation

General information

Usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> I&M data 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal can be configured/integrated as of version 	V11 SP2 / V13
<ul style="list-style-type: none"> STEP 7 can be configured/integrated as of version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision 	GSD Revision 5
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	V2.3 / -

CiR - Configuration in RUN

Reparameterization possible in RUN	Yes
------------------------------------	-----

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, max.	150 mA
---------------------------	--------

Power losses	
Power loss, typ.	1.5 W
Address area	
Address space per module	
• Address space per module, max.	8 byte
Analog outputs	
Number of analog outputs	4
Voltage output, short-circuit current, max.	45 mA
Cycle time (all channels), min.	5 ms
Output ranges, voltage	
• 0 to 10 V	Yes; 15 bit
• 1 to 5 V	Yes; 13 bit
• -5 to +5 V	Yes; 15 bit incl. sign
• -10 to +10 V	Yes; 16 bit incl. sign
Output ranges, current	
• 0 to 20 mA	Yes; 15 bit
• -20 to +20 mA	Yes; 16 bit incl. sign
• 4 to 20 mA	Yes; 14 bit
Connection of actuators	
• for voltage output two-wire connection	Yes
• for voltage output four-wire connection	Yes
• for current output two-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	2 k Ω
• with voltage outputs, capacitive load, max.	1 μ F
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH
Destruction limits against externally applied voltages and currents	
• Voltages at the outputs	30 V
Cable length	
• Cable length, shielded, max.	1 000 m; 200 m for voltage output
Settling time	
• for resistive load	0.1 ms
• for capacitive load	1 ms
• for inductive load	0.5 ms
Errors/accuracies	
Linearity error (relative to output range), (+/-)	0.03 %
Temperature error (relative to output range), (+/-)	0.005 %/K
Crosstalk between the outputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to output area), (+/-)	0.05 %

Operational limit in overall temperature range	
• Voltage, relative to output area, (+/-)	0.5 %
• Current, relative to output area, (+/-)	0.5 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output area, (+/-)	0.3 %
• Current, relative to output area, (+/-)	0.3 %
Interrupts/diagnostics/status information	
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostics	Yes
• Monitoring the supply voltage	Yes
• Wire break	Yes
• Short circuit	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; Green LED
• Channel status display	Yes; Green LED
• for module diagnostics	Yes; Green/red LED
Galvanic isolation	
Electrical isolation channels	
• between the channels	No
• between the channels and the backplane bus	Yes
• between the channels and the supply voltage of the electronics	Yes
Permissible potential difference	
between different circuits	75 V DC/60 V AC (base isolation)
Isolation	
Isolation checked with	707 V DC (type test)
Ambient conditions	
Ambient temperature in operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C
Dimensions	
Width	15 mm
Weights	

Weight, approx.

31 g

last modified:

16.01.2015