



SIMATIC DP, ET 200ECO PN, 8 DI 24V DC;
4 X M12, DOUBLE-ASSIGNMENT,
DEGREE OF PROTECTION IP67;

General information

Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H

Supply voltage

24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, typ.	100 mA
----------------------------------	--------

Encoder supply

Number of outputs	4
Output current, rated value	100 mA ; per output

24 V encoder supply

Short-circuit protection	Yes
---------------------------------	-----

Power losses

Power loss, typ.	5.5 W
-------------------------	-------

Digital inputs

Number of digital inputs	8
In groups of	2
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
up to 60 °C, max.	8
Input voltage	
Type of input voltage	DC
Rated value, DC	24 V
for signal "0"	-3 to +5 V
for signal "1"	11 to 30 V
Input current	
for signal "0", max. (permissible quiescent current)	1.5 mA
for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
at "0" to "1", max.	typically 3 ms
at "1" to "0", max.	typically 3 ms
Cable length	
Cable length unshielded, max.	30 m
Interfaces	
Transmission procedure	100BASE-TX
Transmission rate, max.	100 Mbit/s
Supports protocol for PROFINET IO	
Number of PROFINET interfaces	1
Autocrossing	Yes
Automatic detection of transmission speed	Yes
Integrated switch	Yes
PROFINET IO Device	
IRT with the option "high flexibility" supported	Yes
Prioritized startup supported	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
Supports protocol for PROFI-safe	No
Protocols (Ethernet)	
SNMP	Yes

DCP	Yes
LLDP	Yes
ping	Yes
arp	Yes
Interrupts/diagnostics/status information	
Status indicator	Yes ; Green LED
Alarms	
Diagnostic alarm	Yes
Diagnostic messages	
Diagnostic functions	Yes
Diagnostic information readable	Yes
Monitoring the supply voltage	Yes ; Green "ON" LED
Wire break in signal transmitter cable	Yes
Short circuit encoder supply	Yes ; Per channel group
Group error	Yes ; Red/yellow "SF/MT" LED
Galvanic isolation	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Galvanic isolation digital inputs	
between the channels	No
Isolation	
tested with	
24 V DC circuits	500 V
Interface	1500 V ; According to IEEE 802.3
Degree and class of protection	
IP65	Yes
IP66	Yes
IP67	Yes
Connection method	
M12	Yes
Dimensions	
Width	30 mm
Height	200 mm
Depth	49 mm
Weights	
Weight (without packaging)	550 g
Status	Jan 23, 2014