



Figure similar

SIMATIC S7,SM 332 ANALOG OUTPUT CHANNEL TO CHANNEL ISOLATION, 4 AO, 16 BIT RESOLUTION, 0-10V, 1-5V, +/-10V, +/-20MA, 0/4 - 20MA, 20 PIN, FIT FOR ISOCHRON MODE IMPROVED DP-CYCLE TIME FOR ISOCHRON MODE

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
Input current	
from load voltage L+ (without load), max.	290 mA
from backplane bus 5 V DC, max.	120 mA
Power losses	
Power loss, typ.	3 W
Analog outputs	
Number of analog outputs	4; Isochronous mode
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	40 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 kΩ

• with voltage outputs, capacitive load, max.	1 µF
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH
Cable length	
• shielded, max.	200 m
Analog value creation	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Conversion time (per channel)	200 µs; in isochronous mode 640 µs
Settling time	
• for resistive load	0.2 ms
• for capacitive load	3.3 ms
• for inductive load	0.5 ms
Errors/accuracies	
Operational limit in overall temperature range	
• Voltage, relative to output area, (+/-)	0.12 %
• Current, relative to output area, (+/-)	0.18 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output area, (+/-)	0.02 %
• Current, relative to output area, (+/-)	0.02 %
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostic messages	
• Diagnostic information readable	Yes
• Diagnostics	Yes; Diagnostic information readable
Diagnostics indication LED	
• Group error SF (red)	Yes
Galvanic isolation	
Galvanic isolation analog outputs	
• between the channels and the backplane bus	Yes
Isolation	
Isolation checked with	1500 V DC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm

Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	220 g
last modified:	24.02.2015