

# SIEMENS

## Product data sheet

**6ES7341-1AH02-0AE0**


SIMATIC S7-300,  
CP341 COMMUNICATION PROCESSOR WITH  
RS232C INTERFACE (V.24) INCL. CONFIG.  
PACKAGE ON CD

Supply voltage	
Power supply / Input / Input voltage	
24 V DC	Yes
Power supply / Input / Input current	
from backplane bus 5 V DC, max.	70 mA
from supply voltage L+, max.	100 mA
Power losses	
Power loss, typ.	1.6 W
Power loss, max.	2.4 W
Interfaces	
Number of interfaces	1 ; Isolated
Interface physics, RS 232C (V.24)	Yes
Transmission rate, max.	115.2 kbit/s
Transmission speeds, min.	0.3 kbit/s
Point-to-point	

Cable length, max.	15 m
supported printers	Serial printers
PtP	9-pin sub D connector
<b>Integrated protocol driver</b>	
3964 (R)	Yes
ASCII	Yes
RK512	Yes
<b>Telegram length, max.</b>	
3964 (R)	4096 byte
ASCII	4096 byte
RK 512	4096 byte
<b>Transmission speed, RS232</b>	
with 3964 (R) protocol, max.	115.2 kbit/s
with ASCII protocol, max.	115.2 kbit/s
with printer driver, max.,	115.2 kbit/s
with RK 512 protocol, max.	115.2 kbit/s
<b>Software</b>	
<b>Block</b>	
FB length in RAM, max.	6100 byte ; Data communication, sending and receiving
<b>Connection method</b>	
Power supply	3 screw terminals: L+, M, GND
<b>Dimensions and weight</b>	
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weight</b>	
Weight, approx.	300 g
Status	Mar 14, 2011